			TAW WAT	ER WELL REC	CORD	Form WW	C-5	KSA 82a-				
1 LOCATIO	ON OF WAT	R WELL:	Fraction			1		Number	Township		Range Number	
County:	Rust	<u> </u>	NE SW		14 SE		<u> 19</u>		т 18	3 s	R 20 KW	
			wn or city street f Alexan		и и locati	ea within cit	y r					
	WELL OW				James	Broml	.OW					
RR#, St. Address, Box # :					615 E 5th				Board of Agriculture, Division of Water Resources			
City, State,	•	:		I	LaCro	sse,Ks	. 6	7548	Applicati	on Number:	7327	
J LOCATE AN "X"	WELL'S LO	CATION WITH BOX:	Depth(s) Groun	ndwater Encour	ntered	1		ft. 2		ft. :	3ft.	
- 1 Mile	- NW	- NE	Est. Yield Bore Hole Dia	mp test data: 3.00. gpm: meter28. LTO BE USED	Well wat Well wat in. to AS:	ter was ter was 5 Public v 6 Oil field	. 42	ft. af ft. af ft., a pply upply	ter3. ter3. ind B Air conditioning Dewatering	hours po hours po ir ng 11	umping gpm umping 3.00. gpm h. to ft. Injection well Other (Specify below)	
	- 344	36	2 Irrigation									
1	i 1	1	Was a chemica	al/bacteriologica	al sample	submitted t	o Depart	ment? Ye	sNo	K; If yes	s, mo/day/yr sample was sub-	
I -	S		mitted					Wat	er Well Disinfed	ted? Yes	No X	
5 TYPE C	F BLANK C	ASING USED:		5 Wrought	iron	8 Co	ncrete ti	le	CASING J	OINTS: Glue	d Clamped	
 1 Ste	el	3 RMP (S	SR)	6 Asbestos	-Cement			cify below			ded	
2 PV	С	4 ABS		7 Fiberglas	ss					Thre	aded	
Blank casir	ng diameter	1.6	in. to	42 ft., Di	a	in	, to		ft., Dia		in. to ft.	
Casing heigh	ght above la	nd surface	12"	in., weight.	SDR	2.3.2.5.		lbs./f	t. Wall thicknes	s or gauge N	lo	
-	-		N MATERIAL:				PVC			sbestos-cem		
1 Ste		3 Stainles		5 Fiberglas	SS		RMP (S	SR)	11 O	ther (specify)	
2 Bra		4 Galvani		6 Concrete		9	ABS	,	12 N	one used (o		
_		ATION OPENII				zed wrappe	d		8 Saw cut	•	11 None (open hole)	
	ntinuous slot		Mill slot			wrapped	-		9 Drilled holes		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	uvered shutte		Key punched			ch cut						
		n HTERVALS	tey puriciled	42	/ 1010	57		# E-0-	10 Other (spec		toft.	
G	SRAVEL PAC	K INTERVALS) . <i>.</i>	ft., Fron	n	ft. ft.	toft. toft. to ft.	
	MATERIAL			2 Cement g			entonite					
			ft. to 0		om						ft. to	
		4 Late		7 P i	t privy			11 Fuel s	storage	15 (Oil well/Gas well	
· · · · · · · · · · · · ·			s pool		8 Sewage lagoo				zer storage		Other (specify below)	
		er lines 6 See	•		edyard	3 00			icide storage		none	
Direction fr	-	, 11163 0 000	page p.	0.0	o de y di c			How mar	•		iotie	
FROM	TO TO		LITHOLOGI	C LOG		FROM		TO TO		PLUGGING	INTERVALS	
0	3	Top s									INTERVALS	
3	28		brown cl	 ау								
28	43		and grav									
43	49		clay mix									
49	55	Sand	and grav	el dark	cold	ored c	lav n	nixed				
55	56 ¹ / ₂		and grav			i	1					
	57	Shale										
56½	7.1	Sugre	<u> </u>									
<u> </u>	 						1					
	 											
								+				
	ļ <u>-</u>											
	ļ							- +				
	<u> </u>						1					
completed	on (mo/day/	year)	3-21-96	Ď			. and	I this reco	rd is true to the	best of my k	ider my jurisdiction and was nowledge and belief. Kansas	
			134.								96	
i .	business nar	-	sencrantz					by (signat	^		Godson	
INICTOLI	CTIONS: Use the	nouritor or half poin		S FIRMLY and PRIL	VT clearly. I	Please fill in bla	nks under	line or circle	the correct answers	. Send top three	e copies to Kansas Department	