

MW-9
1 LOCATION OF WATER WELL: County: Rush Fraction: SE 1/4 SW 1/4 SE 1/4 Section Number: 20 Township Number: T 18 S Range Number: R 20 EW
Distance and direction from nearest town or city street address of well if located within city? 96 Highway: Alexander
2 WATER WELL OWNER: RR#, St. Address, Box #: Farmers Coop Oil & Supply 96 Highway Alexander, KS 67513 Board of Agriculture, Division of Water Resources Application Number:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the SE section of the SW quarter]
4 DEPTH OF COMPLETED WELL: 40.0 ft. ELEVATION: 32.0 ft. Depth(s) Groundwater Encountered: 1. 32.0 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 31.82 ft. below land surface measured on mo/day/yr: 1-27-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Flush Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft. Casing height above land surface: Flush in. weight: 703 lbs./ft. Wall thickness or gauge No.: 154 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 25.0 ft. to 340.0 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 24.0 ft. to 40.0 ft. From ft. to ft. From ft. to ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout intervals: From 24.0 ft. to 1.0 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? Northwest How many feet? 100'
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS
0.0 3.5 fill, Clay
3.5 13.5 Clay
13.5 18.5 Clay, slightly silty
18.5 23.5 Clay, silty
23.5 33.5 Clay, silty
33.5 40.0 Sand, fine to medium grain, well to moderately sorted
Flush Mount Waiver granted 12-10-92 for Farmers Coop Oil & Supply; KDHE 01083598 by Don Taylor
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-27-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 1-28-93 under the business name of GSI by (signature) Allison J. Jwin