


MW-6 GSI 2011038 WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Rush		SE 1/4 SW 1/4 SE 1/4	20	T 18 S	R 20 EW
Distance and direction from nearest town or city street address of well if located within city?					
96 Highway, Alexander					
2 WATER WELL OWNER:		Farmers Coop Oil & Supply			
RR#, St. Address, Box # :		96 Highway			
City, State, ZIP Code :		Alexander, KS 67513			
Board of Agriculture, Division of Water Resources		Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 39.5 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 32.0 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 30.32 ft. below land surface measured on mo/day/yr 1-27-93			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 8 in. to ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter in. to ft. Dia		7 Fiberglass			
Casing height above land surface Flush ft. weight 703 lbs./ft. Wall thickness or gauge No. 154		Casing JOINTS: Welded Threaded Flush			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS:		From 24.5 ft. to 39.5 ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 23.5 ft. to 39.5 ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 23.5 ft. to 1.0 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard					
Direction from well? South		How many feet? 110			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0.0 3.5 fill, Clay					
3.5 18.5 Clay					
18.5 23.5 Clay, slightly silty					
23.5 28.5 Clay, white streaks & crystals					
28.5 33.5 Clay					
33.5 39.5 Sand, fine to medium grain well sorted					
Flush Mount waiver granted on 12-10-92 for farmers Coop Oil & Supply; KDHE 01083598 by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-27-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 1-28-93 under the business name of GSI by (signature) Allison Irwin					