


1 LOCATION OF WATER WELL: County: Rush Fraction: SE 1/4 SW 1/4 SE 1/4 Section Number: 20 Township Number: T 18 S Range Number: R 20 E/W

Distance and direction from nearest town or city street address of well if located within city? 96 Highway, Alexander

2 WATER WELL OWNER: RR#, St. Address, Box #: Farmers Coop Oil & Supply Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Alexander, KS 67513 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 39.0 ft. ELEVATION: 31.0 ft.
Depth(s) Groundwater Encountered: 1. 29.78 ft. 2. 31.0 ft. 3. 1-27-93 ft.
WELL'S STATIC WATER LEVEL: 29.78 ft. below land surface measured on mo/day/yr
Pump test data: Well water was 8 in. to 8 ft. after 1-27-93 hours pumping 1-27-93 gpm
Est. Yield 8 gpm: Well water was 8 in. to 8 ft. after 1-27-93 hours pumping 1-27-93 gpm
Bore Hole Diameter: 8 in. to 8 ft. and 8 in. to 8 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted No X
Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Threaded Clamped
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Flush
Blank casing diameter 2 in. to 2 ft. Dia. 2 in. to 2 ft. Dia. 2 in. to 2 ft. Dia. 2 in. to 2 ft. Dia.
Casing height above land surface: Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)
7 Torch cut
SCREEN-PERFORATED INTERVALS: From 24.0 ft. to 39.0 ft. From 24.0 ft. to 39.0 ft. From 24.0 ft. to 39.0 ft. From 24.0 ft. to 39.0 ft.
GRAVEL PACK INTERVALS: From 23.0 ft. to 39.0 ft. From 23.0 ft. to 39.0 ft. From 23.0 ft. to 39.0 ft. From 23.0 ft. to 39.0 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout intervals: From 23.0 ft. to 1.0 ft. From 23.0 ft. to 1.0 ft. From 23.0 ft. to 1.0 ft. From 23.0 ft. to 1.0 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? East How many feet? 200

FROM TO		LITHOLOGIC LOG	FROM TO	PLUGGING INTERVALS
0.0	3.5	fill, Clay		
3.5	8.5	Clay		
8.5	18.5	Clay, Silty		
18.5	24.0	Clay		
24.0	28.5	Clay, silty		
28.5	33.5	Clay, Silty		
33.5	39.0	Sand, Fine to coarse, poorly sorted		
Flush Mount waiver granted on 12-10-92 for Farmers Coop Oil & Supply; RDHE 01083598 by Don Taylor				

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-27-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 1-28-93 under the business name of GSI by (signature) Alison Irwin