


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: Ness Fraction: NW 1/4 SW 1/4 SW 1/4 Section Number: 1 Township Number: T 18 S Range Number: R 21 EW

Distance and direction from nearest town or city street address of well if located within city?
Approx. 3 miles North and 3 miles West of Alexander, KS

2 WATER WELL OWNER: Wet Walnut Watershed
 RR#, St. Address, Box #: 108 West 8th
 City, State, ZIP Code: LaCrosse, KS 67548
 Board of Agriculture, Division of Water Resources
 Application Number: not required

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 24 ft. ELEVATION: unknown
 Depth(s) Groundwater Encountered: 1. 8 ft. 2. 8 ft. 3. 8 ft.
 WELL'S STATIC WATER LEVEL: 8 ft. below land surface measured on mo/day/yr: 4/27/83
 Pump test data: Well water was not checked after 0 hours pumping 0 gpm
 Est. Yield: unknown gpm: Well water was 0 ft. after 0 hours pumping 0 gpm
 Bore Hole Diameter: 9 in. to 24 ft., and 0 in. to 0 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well and stock
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes XX No XX; If yes, mo/day/yr sample was submitted 0
 Water Well Disinfected? Yes XX No XX

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XXX Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to 11 ft., Dia. 5 in. to 24 ft., Dia.
 Casing height above land surface: 24 in., weight 2.277 lbs./ft. Wall thickness or gauge No. .214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 11 ft. to 21 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 10 ft. to 24 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage PASTURE LAND
 Direction from well? all How many feet? 0

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	11 <u>01</u>	Topsoil & tan clay			
11	16 <u>17</u>	Sand & gravel, med. w/broken limestone w/a couple streaks of clay			
16	20 <u>01</u>	Tan clay			
20	21 <u>17</u>	Sand & gravel, med. w/broken limestone			
21	24 <u>21</u>	Gray shale w/a real hard streak of limestone @ 21'			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/27/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 5/2/83 under the business name of Clarke Well & Eq., Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

18

R

21

EW

SEC.

1

NW 1/4

SW 1/4

SW 1/4

DP