	WA	TER WELL REC	ORD Form WW	C-5 KSA 82	2a-1212 ID N	lo		
1 LOCATION OF W		Fraction			Section Number	Township Numb	per Range	Number
County: NES	S	NE ¼	NE ¼ S	E 1/4	24	т 18	S R 24	yE/W
Distance and direction	n from nearest to				?			
	1	/2 MILE	WEST OF NE	SS CTTV				
2 WATER WELL O	****	MAN REILE						
RR#, St. Address, Bo						Board of Agricu	ulture, Division of Wat	ter Resources
City, State, ZIP Code		- ·				Application Nur	,	ter riesources
3 LOCATE WELL'S L	OCATION WITH	ESS CITY 41 DEPTH OF C	KS 67560 OMPLETED WELL	35	ft. ELEVA	ATION:		
AN "X" IN SECTION		Denth(s) Group	dwater Encountered	_{d 1} 21	f	t. 2	ft 3	ft
N		WELL'S STATIC	CWATER LEVEL	2 1	pelow land surfa	ce measured on mo/da	y/yr	U.3
	'	Pun	np test data: Well	water was	ft.	after	hours pumping	gpm
NW	NE					after		gpm
1	ı	1 Domestic	TO BE USED AS: 3 Feedlot	6 Oil field wat	er supply	8 Air conditioning 9 Dewatering	11 Injection well12 Other (Specify	helow)
w !	E	2 Irrigation	4 Industrial			10 Monitoring well		
	X					ū		
sw	SE	Was a chemical	/bacteriological san	nnle submitted	to Department?	Vee No XX · I	f vee mo/day/vre ear	mnle was sub-
Was a chemical/bacteriological sample submitted to Department? Yes Noxx; If yes, mo/day/yrs sample was su Water Well Disinfected? Yes No xx								
5 TYPE OF BLANK	CACINO HEED.		E Manualitian	0.00		OACINO JOINT	S: GluedXX. Clar	
5 TYPE OF BLANK	CASING USED: 3 RMP (S		5 Wrought iron6 Asbestos-Ceme		ncrete tile er (specify belov		Welded Uar	•
%×P¥C	4 ABS	,	7 Fiberglass			*/	Threaded	
	r5.	in. to	_			ft., Dia	in. to	ft.
						. lbs./ft. Wall thickness		
TYPE OF SCREEN (OR PERFORATIO	N MATERIAL:	_	χ7x	£XVC	10 Asbesto	os-Cement	
1 Steel 3 Stainless Steel 5 Fibe						11 Other (Specify)		
2 Brass	4 Galvania	zed Steel	6 Concrete tile	9	ABS	12 None u	ised (open hole)	
SCREEN OR PERFO	RATION OPENI	NGS ARE:		Guazed wrappe	ed	8 Saw cut	11 None (or	pen hole)
1 Continuous slot 3x/₩ilkslot				6 Wire wrapped		9 Drilled holes		
2 Louvered shut	ter 4 K	(ey punched		Torch cut		10 Other (specify)		
SCREEN-PERFORA	TED INTERVALS					1		
CDAVEL B	ACK INTEDVALO))		
GRAVELP	ACK INTERVALS	From	ا الله الله الله الله الله الله الله ال)	ft., From)	ft. to	
6 GROUT MATER		t cement	2 Cement grout			4 Other		
Grout Intervals: From	om0	ft. to	25 ft., From		ft. to	ft., From	ft. to	ft.
What is the nearest s	ource of possible	contamination:			10 Lives	stock pens	14 Abandoned wa	ater well
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel	storage	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertil	izer storage	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit			9 Fee	9 Feedyard		cticide storage		
Direction from well?					How ma	ny feet?		
FROM TO		LITHOLOGIC	LOG	FROM	ТО	PLUGG	SING INTERVALS	
0 5	surfac	ce clay						
5 20	HARD (GRAY CLAY						
20 25	FINE S	SAND						
25 32	MED SZ							
32 35		SHALE						
7 CONTRACTOR'S	OR LANDOWNE	R'S CERTIFICAT	ION: This water we	ellwas (1%)r syona	structed, (2) red	onstructed, or (3) pluge	ged under mv iurisdi	ction and was
						ecord is true to the best		
						ed on (mo/day/ʃr)\		
under the business na	me of AND	Y ANDEDS	ON DRILLIN	C	by	(signature) (Luca	la (and ex	3un
	pewriter or ball point pe	en. <i>PLEASE PRESS FI</i>	RMLY and PRINT clearly.	Please fill in blanks,		e correct answers. Send top thr	ree copies to Kansas Depart	rtment of Health
	u of Water, Geology Se	ection, 1000 SW Jackso				5522. Serid one to WATER WE		