			WATE	R WELL RECORD	Form WWC-5	KSA 82a-	1212	71	n <i>u 9</i> 5	
1 LOCATION	_	_	Fraction		Sec	tion Number	r Township Nu		Range Number	
County: Distance and		ess om nearest	NW ½ town or city street add	ress of well if loca	SE ½ ted within city? n, Beeler, Kan	33	<u>T 18</u>	S	R 26	E
2 WATER W	FIL OWN	R· KDF	IE Time and Ma			1545				
RR#, St. Addr			SW Jackson #		. осор		Poord of Acris	Huma Divisia	a of Water Decemb	
City State 711	Codo	Top	oka Ke 66612-			÷			n of Water Resourc	es
3 LOCATE W	VELL'S LO	CATON WI	THI		,		Application Nur			\dashv
3 AN "X" IN S	SECTION E	BOX:		OMPLETED WELI	45	ft. ELE	VATION:			Ì
			Depth(s) Groundy	water Encountered	1 35	1	it. 2 surface measured or	Ft. 3		Ft.
	N		WELL'S STATIC	WATER LEVEL _	36.88 ft.	below land:	surface measured o	ı mo/day/уг ့	10/29/03	1
†			Pump	test data: Well v	water was		Ft. after	hours pum	ping G	om
	NW	NF	Est. Yield	Gpm: Well v	water was		Ft. after Ft. after ft. and	Hours pum	ping G	om i
	i	- i	Bore Hole Diamet	ter 8.625 In.	to 42	.5	ft. and	in. to		Ft.
₩ W	+	—' ∡ —	Bore Hole Diamet WELL WATER TO 1 Domestic	D BE USED AS:	5 Public water s	upply	8 Air conditioni	ng 11 ir	njection well	! ا
ī 1										~,
!	SW	SE					ic) 10 Monitoring			
,	1		Was a chemical/b Submitted	acteriological sam	ple submitted to f		Yes No X			s
5 TYPE OF E	SI ANK CAS	SING LISE		5 Wrought Iron	8 Conor		ater Well Disinfected			\dashv
1 Steel			J. IP (SR)	6 Asbestos-Cer			CASING JOINT			
2 PVC	_	4 AB:	• •		nent 5 Other	(specify beig	^{5W)}	Welded		
2 170		4 AB.	5	7 Fiberglass Ft.,			L	Threade	<u> </u>	
Blank casing d	liameter	2	in. to 22.5	Dia	In. t	0	ft., Dia	in.	to	Ft.
Casing height	above land	surface	FLUSH I	n., weight	SCH 40	Lbs./ft	. Wall thickness or g	auge No.		
TYPE OF SCF	REEN OR F	PERFORAT	ION MATERIAL:		7	PVC	10 Asbes	tos-cement		
1 Steel			inless steel	5 Fiberglass	8	RMP (SR)	11 Other			
2 Brass			vanized steel	6 Concrete tile	9	ABS	12 None	used (open h	ole)	- 1
SCREEN OR F	nuous slot		3 Mill slot		auzed wrapped		8 Saw cut		None (open hole)	'
	red shutter		4 Key punched		Vire wrapped		9 Drilled holes			
SCREEN-PER				0.5	orch cut 42.5		10 Other (specify	"		
OOKELIA LIV	OWILL	INTERVAL		ft. to	42.5	ا ۱۱۰۰۰۰۰۰	From			i
SAND	PACK INT	FRVALS:	From 2		42.5	ا ۱۰۰۰۰۰۰۰	From	IL. TO _		Ft. 2
			From			· ···	From			Ft.
6 GROUT MA	ATERIAL:	1 Nea	at cement 2			tonite	4 Other			-
				Ft.	Ft	-				- 1
Grout Intervals	From3	U	ft. to 18.5	From2	18.5 to	20.	5 ft. From			ft.
			le contamination:	7 D'			tock pens		ned water well	
		4 Lateral lines	-	-	11 Fuel:	_	15 Oil well		_	
2 Sewer lines3 Watertight sewer lines			5 Cess pool		age lagoon		izer storage		specify below)	_
3 Wateri • Direction from	_	ıınes	6 Seepage pit	9 Feed	dyard		ticide storage	Conta	minated Site	ļ
FROM	TO	CODE	LITHOLO	OGIC LOG	FROM	How many TO		GING INTER	D\/AI S	\dashv
0	1		Gravel		11,010	'0	PLUG		NYALO	4
1	8		Silty Clay (CL)							-
8	31		Clayey Silt (ML)	··· <u>-</u>						┥`
31	42.5	5	Silty Sand (SM)							_
42.5	TD	E	nd of Borehole							
						ļ <u>Ī</u>				
	-									_
						 	n			\dashv
				-		† †				\dashv
										\dashv
										\dashv
]
Z LOONITO A CO	TOP'O OC	LANDONE	EDIO OEDTIE:	N. Th						
		LANDOWN	ER'S CERTIFICATIO	n: Ins water well						
Completed on (10/28/	FOE			rue to the best of my	-		
			Accoriate	585	This W		cord was completed			
Inder the busin			nks and circle the correc	d Environme	ree copies to Kanaa	B S Departmen	y (signature) Dari	n K Dunc	an /)/M	4
Kansas 66	620-0001.	Telephone: 9	913-296-5545. Send on	e to WATER WELL	OWNER and retain	one for your	records.	meni, bureau	от учают, горека,	