

1) LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number
County: Lane		SW 1/4	SE 1/4	SW 1/4	18	T 18 S
Distance and direction from nearest town or city street address of well if located within city?		R 28 E/W				
JCM Trucking - 328 Long Steet - Dighton, KS						
2) WATER WELL OWNER: Presta Oil Company						
RR#, St. Address, Box # : P.O. Box 1709				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Garden City, Kansas 67846				Application Number:		
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL 65 ft. ELEVATION: 2763.57				
		Depth(s) Groundwater Encountered 1. 999 ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 999 ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was NA ft. after hours pumping gpm				
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter 8 in. to 65 ft., and in. to ft.				
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well				
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....		If yes, mo/day/yr sample was submitted				
Water Well Disinfected? Yes No						
5) TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped		
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded		
Blank casing diameter 2 in. to 65 ft., Dia in. to ft., Dia in. to ft.		7 Fiberglass		Threaded.		
Casing height above land surface -2.16 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40						
TYPE OF SCREEN OR PERFORATION MATERIAL						
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)						
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)				
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 43 ft. to 65 ft., From ft. to ft.						
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 39 ft., From 39 ft. to 43 ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
Direction from well? SW		13 Insecticide storage Former UST Basin				
How many feet? 385						
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS						
0 9 Clay, Brown						
9 34 Caliche, White to Tan						
34 44 Sand, Light Brown						
44 61 Sand, Brown to Red Brown						
61 65 Chalk, Tan						
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/29/96 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 9/28/96						
under the business name of GeoCore Services, Inc. by (signature) [Signature]						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						