WATER WELL R	ECORD	Form W	WC-5	Division of Wate	er Resources App. N		
1 LOCATION OF W County: McPher	son	Fraction  1/4 NW 1/4 NE		Section Number <b>7</b>	Township No. T 18 S	Range Number R 3	
	if unknown, distance	Global Positioning					
from nearest town or intersection: If at owner's address, check here				Latitude: (in decimal degrees) Longitude: (in decimal degrees) Elevation:			
2 WATER WELL OWNER: Mike Becker				Datum: WGS 8 Collection Method:	4, NAD 83,	] NAD 27	
RR#, Street Address, Box #: 1210 Sioux Rd.			GPS unit (Make/Model:)				
City, State, ZIP Code : Lindsborg, KS 67456			☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 80 ft.							
SECTION BOX:	FION BOX: Depth(s) Groundwater Encountered (1)						
N	WELL'S STATIC WATER LEVEL30 ft. below land surface measured on mo/day/yr.10/26/11  Pump test data: Well water was						
EST. YIELD. 2-3. gpm. Well water was							
W Bore Hole Diameter 9 in. to 80 ft., and in. to ft.  WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							
Sw Sp Domestic Feedlot Oil field water supply Dewatering X Other (Specify below)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Stock  Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☒ No							
S If yes, mo/day/yr sample was submitted							
1 mile  Water well disinfected? ▼ Yes □ No							
5 TYPE OF CASING USED: Steel X PVC Other Other CASING JOINTS: X Glued Clamped Welded Threaded							
CASING JOINTS: A Glued Clamped Welded Threaded Casing diameter 5 in to 40 ft., Diameter in to ft. Casing height above land surface 12 in, Weight 2.37 lbs./ft., Wall thickness or gauge No							
Casing height above land surface!4							
Steel Stainless Steel YPVC Other (Specify)							
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:							
Continuous slot XX Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)							
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From ft. to 80 ft., From ft. to ft.							
From							
From ft. to ft. From ft. to ft.							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other.  Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:							
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)  Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well							
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedward    ☐ Fertilizer storage ☐ Oil well/gas well							
Direction from well FROM TO	LITHOLOG	***************************************	Distance FROM	from wellTO LITHO. L		JGGING INTERVALS	
0 2 Top	soil				and the second s		
	y, gray				Market and the second		
	le, gray le, red					TO SERVICE AND	
	le, gray w/sm	all fractures					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was \( \bigs_1 \) constructed, \( \bigs_1 \) reconstructed, or \( \bigs_1 \) plugged under my jurisdiction and was completed on \( \bigs_1 \) day/year \( \bigs_2 \) 10/26/11 and this record is true to the best of my knowledge and belief.							
under my jurisdiction and was completed on (mo/day/year)							
under the business name of Peterson Irrigation, Inc. by (signature)							
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell/index.html.							
KSA 82a-1212							