

1 LOCATION OF WATER WELL: Fraction SW 1/4 SW 1/4 SE 1/4 Section Number 17 Township Number T 18 S Range Number R 32 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Gene Gamble
 RR#, St. Address, Box #: 106 W. Glenn Ave.
 City, State, ZIP Code: Scott City, Ks. 67871
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SE quadrant. A vertical scale on the left indicates 1 Mile.]

4 DEPTH OF COMPLETED WELL: 168 ft. ELEVATION: ... ft.
 Depth(s) Groundwater Encountered 1. ... ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL: 105 ft. below land surface measured on mo/day/yr 5-28-93
 Pump test data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield: 36 gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter: 10 in. to 168 ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS:
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes ... No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped ...
 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded ...
 Threaded ...
 Blank casing diameter: 5 in. to 168 ft., Dia. ... in. to ... ft., Dia. ... in. to ... ft.
 Casing height above land surface: 12 in., weight ... lbs./ft. Wall thickness or gauge No. 200 psi
 TYPE OF SCREEN OR PERFORATION MATERIAL: 5' of draw down PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ...
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ...
 SCREEN-PERFORATED INTERVALS: From 138 ft. to 168 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 168 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout Bentonite chips 3 Other ...
 Grout Intervals: From 5 ft. to 25 ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination:
 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	top soil			
1	56	brown clay & gypsum			
56	61	fine sand			
61	74	brown clay & gypsum			
74	108	fine to medium sand & coarse sand			
108	137	brown clay			
137	142	fine sand			
142	167	fine to medium sand, coarse sand & gravel			
167	168	yellow clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-28-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 532 This Water Well Record was completed on (mo/day/yr) 6-4-93 under the business name of Midwest Well & Pump by (signature) Victor Jankup

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.