WATER WELL RECORD Form WWC-5 KSA 82a-1212

					ATION												
	241 10012334	Box # : P							Board	dof	Agricu	lture,	Divisi	on of	Water R	esource	!S
City,	State, ZIP	code : S	COTT CITY,	KS	67871-				Appli	icati	on Nue	ber:				80 min han 40 min 940 mi	
AH "X"	WELL'S LOC IN SECTION		1							LEVAT:		0 ft.	2.	0 f	t.	3.	0 ft
 \	 	1. 1	! 				R LEVEL										05/91 0 gp
				Estim	ated Yie	ld	O gpm:	Well (water (va s	0 f	t. aft	er	0 hour	s pumpi	ng	0 g p
	 	• •	E	Bore	Hole Dia	meter		B i	in. to	13	5 ft.,	and	in	. to	0 ft	•	
• I	 SW			WELL	WATER TO	BE US	BED AS:	10 MON	ITORIN	9							
ı			; ;									,**					
TYPE O Blank Casing TYPE O SCREEN	 	I I - ING USED: OF eter 2 ve land sur PERFORATION TION OPENING	PVC in to face -4 MATERIAL:	If ye 11 in., 07 P 03 N	s, mo/da CA 5 ft., wei VC ILL SLOT	y/yr s SIMG J Dia ght	OINTS: in. 3 lbs	THREADI to /ft. i	ED Oft.	., Di hickm	ia 255 OT	in. gauge	Wa to	ter we	ll disi	nfected	1? Ho
TYPE O Blank Casing TYPE O SCREEN	F BLANK CAS casing diam height abo F SCREEN OR H OR PERFORA	I I - ING USED: Or eter 2 ve land sur PERFORATION TION OPENIM	PVC in. to face -4 MATERIAL:	If ye	s, mo/da CA 5 ft., wei VC ILL SLOT 115 ft. 0 ft. 99 ft.	sy/yr s	FOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft.	THREADI to /ft. i	ED Oft.	ft. f	ia ess or to to	in. gauge	Wa to	ter we		nfected	1? Ma
TYPE 0 Blank Casing TYPE 0 SCREEN SCREEN	OF BLANK CAS casing diam height abo OF SCREEN OR OR PERFORA PERFORATED GRAVEL PACK MATERIAL Intervals:	I I	PVC in. to	If ye 11 in., 07 P 03 M rom rom rom 99 ft	S, mo/da CA S ft., wei VC ILL SLOT 115 ft. 0 ft. 99 ft. 0 ft.	SING J Dia ght to to to	TOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. i From From From	mitted ED Oft. Wall th	ft. ft. ft.	ia ess or to to	in. gauge Oft. Oft. Oft.	to No2	ter we			1? No
TYPE O Blank Casing TYPE O SCREEN SCREEN GROUT Grout What i	F BLANK CAS casing diam height abo F SCREEN OR OR PERFORA PERFORATED GRAVEL PACK	I I I I I I I I I I I I I I I I I I I	PVC in. to face -4 MATERIAL: GS ARE: F F F F F F F F F F F F F	If ye 11 in., 07 P 03 M rom rom rom 99 ft	S, mo/da CA S ft., wei VC ILL SLOT 115 ft. 0 ft. 99 ft. 0 ft.	SING J Dia ght to to to	TOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. i From From From	mitted ED Oft. Wall th	ft. ft. ft.	ia ess or to to	in. gauge O ft. O ft. O ft.	to No2	0 ft. 65			
TYPE O Blank Casing TYPE O SCREEN SCREEN GROUT Grout What i Direct	F BLANK CAS casing diam height about the perforated GRAVEL PACK MATERIAL Intervals: is the nearestion from weight to the perforance of th	I I I I I I I I I I I I I I I I I I I	PVC in. to face -4 H MATERIAL: SS ARE: F F F F F F F F F F F F F F F F F F	If ye 11 in., 07 P 03 M rom rom rom 99 ft	s, mo/da CA 5 ft., wei VC ILL SLOT 	SING J Dia ght to to to	TOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. I	mitted ED Oft. Wall th	ft. fft. fft. f	ia ess or to to	in. gauge O ft. O ft. O ft.	to No2	0 ft. 65		feet?	
TYPE O Blank Casing TYPE O SCREEN SCREEN GROUT Grout What i Direct FROM 0	DF BLANK CAS casing diam height abor DF SCREEN OR H OR PERFORATED GRAVEL PACK MATERIAL Intervals: is the neare tion from we i TO i 8 i 16	I I I I I I I I I I I I I I I I I I I	P PVC in. to face -4 N MATERIAL: GS ARE: F F F F F TE ft. to f possible REA LITH	If ye 11 in., 07 P 03 M rom rom rom 99 ft conta	s, mo/da CA S ft., wei VC ILL SLOT 115 ft. 0 ft. 99 ft, From mination C LOG	SING J Dia ght to to to	TOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. I From From From	enitted ED Oft. Wall the control of the control	ft. fft. fft. f	ia ess or to to	in. gauge 0 ft. 0 ft. 0 ft. t.	to No2	o ft. 65 ft. H	ow many	feet?	
TYPE O Blank Casing TYPE O SCREEN SCREEN GROUT Grout What i Direct FROM 0 8 16	DF BLANK CAS casing diam height about the perforated GRAVEL PACK MATERIAL Intervals: is the neareston from we lead to the perforated to t	ING USED: OF ETERNATION OPENING TION OPENING TO THE STATE OF TIME STATE OF TIME STATE OPENING TO THE STATE OPENING TO THE STATE OPENING THE STATE OPENING THE STATE OF TIME STATE OPENING THE STATE OPE	PVC in. to face -4 N MATERIAL: GS ARE: F F F F F F F F F F F F F	If ye 11 in., 07 P 03 M rom rom rom 99 ft conta	s, mo/da CA S ft., wei VC ILL SLOT 115 ft. 0 ft. 99 ft, From mination C LOG	SING J Dia ght to to to	TOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. I From From From	enitted ED Oft. Wall the control of the control	ft. fft. fft. f	ia ess or to to	in. gauge Oft. Oft. Oft. ft. t	to No2	oft. ft. H GGING	on bany Interva	feet?	
TYPE O Blank Casing TYPE O SCREEN SCREEN GROUT Grout What i Direct FROM 0	DF BLANK CAS casing diam height abo DF SCREEN OR OR PERFORATED GRAVEL PACK MATERIAL Intervals: s the neare ion from me 1 TO 1 8 1 16 1 58 1 96	I I I I I I I I I I I I I I I I I I I	PVC in. to face -4 MATERIAL: GS ARE: FF	If ye 11 in., 07 P 03 M rom rom rom g9 ft conta	S, mo/da CA S ft., Wei VC ILL SLOT 115 ft. O ft. 99 ft. O ft. ., From mination C LOG	SING J Dia ght to to to to	JOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. I From From From	enitted ED Oft. Wall the control of the control	ft. fft. fft. f	ia ess or to to	in. gauge Oft. Oft. Oft. tt. t	to No2 o O PLU 75' v f the	oft. 65 ft. H 66IN6 vest	on many Interval and 3 least	feet? Ls O' sou	
TYPE O Blank Casing TYPE O SCREEN SCREEN GROUT Grout What i Direct FROM 0 8 16 58	F BLANK CAS casing diam height about the performation of PERFORATED GRAVEL PACK MATERIAL Intervals: is the nearestion from we have the performation of the perforation of the performance of the performan	I I I I I I I I I I I I I I I I I I I	PUC in. to face -4 H MATERIAL: SS ARE: FF	If ye 11 in., 07 P 03 M rom rom rom g9 ft conta	S, mo/da CA S ft., Wei VC ILL SLOT 115 ft. O ft. 99 ft. O ft. ., From mination C LOG	SING J Dia ght to to to to	JOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. I From From From	enitted ED Oft. Wall the control of the control	ft. fft. fft. f	ia ess or to to	in. gauge Oft. Oft. Oft. tt. t	to No2 o O PLU 75' v f the	oft. 65 ft. H 66IN6 vest	on bany Interva	feet? Ls O' sou	
TYPE 0 Blank Casing TYPE 0 SCREEN SCREEN GROUT Grout What i Direct FROM 0 8 16 58 96	F BLANK CAS casing diam height about the performance of SCREEN OR FERFORATED GRAVEL PACK MATERIAL Intervals: Is the nearestion from we have the performance of the p	I I I I I I I I I I I I I I I I I I I	PUC in. to face -4 H MATERIAL: SS ARE: FF	If ye 11 in., 07 P 03 M rom rom rom g9 ft conta	S, mo/da CA S ft., Wei VC ILL SLOT 115 ft. O ft. 99 ft. O ft. ., From mination C LOG	SING J Dia ght to to to to	JOINTS: in. 3 lbs 135 ft. 0 ft. 135 ft. 0 ft.	THREADI to /ft. I From From From	enitted ED Oft. Wall the control of the control	ft. fft. fft. f	ia ess or to to	in. gauge Oft. Oft. ft. t	to No2 o O PLU 75' v f the	oft. 65 ft. H GGING vest	on many Interval and 3 least	feet? Ls O' sou	