			WATI	ER WELL REG	COBD F	orm WWC-5	KSA 82	a-1212						
1 LOCATION OF WATER WELL: Fractio			Fraction	ction			Section Number Township Nur				nber Range Number			
	Scott		NW V		14 SW	1/4	21	т	18	S	R	32	B(W)	
Distance a	nd direction	from nearest to	wn or city street	address of we	Il if located	within city?			,					
2 WATER	WELL OW	NER: Tho	mas M.K	irk.	***									
<b>-</b>	Address, Bo	x # : /(L/)	I F FAIR	-					Board of Ag	riculture.	Division	of Water	Resources	
•	ZIP Code	: Gar	den City,	Ks. 67	1846				Application					
		OCATION WITH	4 DEPTH OF	COMPLETED	WELL	132	# ELEV	ΑΤΙΩΝ:						
AN "X"	IN SECTIO	N BOX:	Depth(s) Groun											
ī Г	1		WELL'S STATIO	C WATER LE	VEL	<b>4</b> ft. b	elow land s	urface m	easured on	no/day/yr	<i>3</i> .	-30-	92_	
-	- NW	NE	Pun Est. Yield	np test data:						•				
• w	i	E	Bore Hole Diam											
_						Public water			conditioning		Injection			
I  -	- SW	SE	1 Domestic			Oil field wa			vatering					
1	l×.	1 1	2 Irrigation						nitoring well					
<u> </u>	ŀ		Was a chemical mitted	/bacteriologica	al sample sul	omitted to D			No Il Disinfected	- 1	٠ .	•	e was sub-	
E TVDE (	TO ANK	CASING USED:	Tunnea	5 \4/max.=b4	·	0 Conor						No		
				5 Wrought		8 Concre			CASING JOIN		-	•	1	
1 Ste	-	3 RMP (S	6H)		-Cement		(specify belo					•, • • • • •		
2 PV	-	4 ABS		7 Fiberglas										
			.in. to											
•	•		3 below	in., weight .				./ft. Wal	l thickn <del>es</del> s o	gauge N	<b>1</b> 0			
TYPE OF	SCREEN O	R PERFORATIO	ON MATERIAL:			7 PV	С			stos-cem		. 1 /.		
1 Ste	el	3 Stainles	ss steel	5 Fiberglas	ss ·	8 RM	IP (SR)		11 Othe			, , ,		
2 Bra	ass	4 Galvani	zed steel	6 Concrete	tile	9 AB	S		. 12 None	used (o	pen hole	) *		
SCREEN (	OR PERFO	RATION OPENII	NGS ARE:		5 Gauzed	wrapped		8 Sa	aw çut		11 No	ne (open	hole)	
1 Co	ntinuous sk	ot 3 M	/lill slot		6 Wire wr	apped			illed holes			. 1.		
2 Lo	uvered shut	ter 4 h	Key punched	N/A	7 Torch c			10 O	ther (specify)		1	V/#		
SCREEN-I	PERFORAT	ED INTERVALS	: From	N/A	ft. to	NA	ft., Fr	om		ft.	to		ft.	
ć	RAVFI PA	CK INTERVALS												
•	2. U.V. LL	OK WILLIAME	From		ft. to		ft., Fr						ft	
S GROUT	MATERIAL	· 1 Nest	cement	2 Cement g		3 Bento							- '1.	
Grout Inter			. ft. to 6.											
					Om	n.								
		•	contamination:					stock pe				ed water v	well	
1 Septic tank 4 Lateral lines					t privy		11 Fuel storage			15 Oil well/Gas well				
2 Sewer lines 5 Cess pool			·	8 Se	n	12 Fertilizer storage			16 Other (specify below)					
3 W	atertight sev	er lines 6 See	page pit	9 Fe	edyard		13 Inse	cticide s	storage	<i>.</i>				
Direction f		T						any feet		1000110				
FROM	TO		LITHOLOGIC		<del>. ,</del>	FROM	то		PLU	JGGING	INTERV	ALS		
104	132	wasned sai	nd & gravel	- 11/2 y	as		//							
_6_	104	mixture of	washed Sand	1+grave1	,fill Sa	nd +CL	W-5%	tyds						
3	6	bentonit	e Chips -	- 400	165.			0						
0	3	fill dic.	<i>+</i>											
						,								
									•					
· <u>-</u>							<b> </b>							
										-				
							<del>                                     </del>							
							<b> </b>						1	
				Officer 1951							•			
							<b>.</b>	ļ						
<b></b>							1	l						
7 CONTR	RACTOR'S	OR LANDOWNE	R'S CERTIFICAT	TION: This wa	ter well was	(1) constru	cted, (2) red	construct	ted, or 🕍 pli	ugged un	der my i	urisdiction	and was	
	on (mo/day		3-30-92						ue to the bes					
	-	's License No.	532		s Water Wel						7-92			
		me of Mid		+ Pum			by (sign		With	Sin	bour			
			t pen. <i>PLEASE PRESS</i>			a fill in blanke			ract anomara Co	nd too thice	conia in	Kanese Des	artment	
			r, Topeka, Kansas 666										umdn	