


1 LOCATION OF WATER WELL: County: Scott Fraction: SE 1/4 NE 1/4 NE 1/4 Section Number: 23 Township Number: T 18 S Range Number: R 33 EW

Distance and direction from nearest town or city street address of well if located within city?
1W 1/4 South of Scott City

2 WATER WELL OWNER: Doug Dreiling
 RR#, St. Address, Box #: 1401 College Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Scott City KS 67871 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 165 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 100 ft. 2. 110 ft. 3. 10 ft.
 WELL'S STATIC WATER LEVEL 100 ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 110 ft. after 1 hours pumping 10 gpm
 Est. Yield 20 gpm: Well water was 110 ft. after 1 hours pumping 10 gpm
 Bore Hole Diameter 9 in. to 165 ft., and 9 in. to 165 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded
 Blank casing diameter 5 in. to 145 ft., Dia. 5 in. to 145 ft., Dia. 5 in. to 145 ft.
 Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. SH40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 145 ft. to 165 ft., From 145 ft. to 165 ft., From 145 ft. to 165 ft.
 GRAVEL PACK INTERVALS: From 20 ft. to 165 ft., From 20 ft. to 165 ft., From 20 ft. to 165 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 20 ft., From 0 ft. to 20 ft., From 0 ft. to 20 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? South How many feet? 300

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	Topsoil, cliche and little clay			
16	32	Sand fine			
32	49	Clay and cliche			
49	65	Sand and little clay			
65	82	Clay and little cliche			
82	93	Sand			
93	98	Sandy clay			
98	157	Sand and claiche streaks			
157	162	Yellow clay			
162	165	Shale			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-28-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473. This Water Well Record was completed on (mo/day/yr) 10-10-96 under the business name of Tyler Water Well Service Inc by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.