TYPE OF BLANK CASING USED:  1 Steel  2 PVC  4 ABS  7 Fiberglass  Blank casing diameter  5in. to  140  6 Asbestos-Cement  7 Fiberglass  8 Concrete tile  7 Fiberglass  1 Steel  1 Steel  3 Stainless steel  1 Steel  3 Stainless steel  4 Galvanized steel  5 Fiberglass  8 RMP (SR)  2 Brass  4 Galvanized steel  5 Fiberglass  8 RMP (SR)  9 ABS  8 RMP (SR)  9 ABS  8 RMP (SR)  7 PVC  8 RMP (SR)  9 ABS  8 RMP (SR)  1 Continuous slot  3 Mill slot  4 Key punched  7 Torch cut  8 CREEN-PERFORATED INTERVALS:  From  6 Wire wrapped  7 Torch cut  8 CREEN-PERFORATED INTERVALS:  From  1 100	Board of Agriculture, Application Number:  VATION: t. 2. ft. 3 surface measured on mo/day/yr after hours putafter hours putaft	ft.  f 6/11/86  umping gpm umping gpm n. to ft.  Injection well Other (Specify below) s, mo/day/yr sample was sub-
Distance and direction from nearest town or city street address of well if located within city?    Marienthal, Kensas	Board of Agriculture, Application Number:  VATION:  t. 2	Division of Water Resources  3
WATER WELL OWNER: RR#, St. Address, Box #:  CIty, State, ZIP Code:  DEPTH OF COMPLETED WELL:  DE	Application Number:  VATION:  t. 2. ft. 6 surface measured on mo/day/yr after hours put after	
WATER WELL OWNER:  IR#, St. Address, Box #:  ROUTE 1  Marienthel, Kenses 67863  LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  Depth(s) Groundwater Encountered 1. 129.  WELL'S STATIC WATER LEVEL 129. ft. below land water was bore Hole Diameter 9. in to 160.  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feedlot 6 Oil field water supply 2 Irrigation 4 Industrial 7 Lawn and garden on was a chemical/bacteriological sample submitted to Department mitted  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile 2 PVC 4 ABS 7 Fiberglass  Blank casing diameter 5 in to 140 ft., Dia in to casing height above land surface 12. in, weight 2.9  YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut 5 From 140 ft. to 160 ft., From f	Application Number:  VATION:  t. 2. ft. 6 surface measured on mo/day/yr after hours put after	
R#, St. Address, Box #:  Ity, State, ZIP Code  LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  WELL'S STATIC WATER LEVEL. 129. ft. below land NA Pump test data: Well water was Bore Hole Diameter. 9. in. to 160.  WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 2 Irrigation 4 Industrial 7 Lawn and garden on Was a chemical/bacteriological sample submitted to Department mitted  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify be assing height above land surface 12 in., weight 2.9  YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 7 Torch cut CREEN-PERFORATED INTERVALS: From 140 ft. to 160 ft., From ft. To	Application Number:  VATION:  t. 2. ft. 6 surface measured on mo/day/yr after hours put after	
IN State, ZIP Code  LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  Depth(s) Groundwater Encountered 1. 129.  WELL'S STATIC WATER LEVEL 129. ft. below land NA Pump test data: Well water was Est. Yield gpm: Well water was Est. Yield gpm: Well water supply 2 Irrigation 4 Industrial 7 Lawn and garden on Was a chemical/bacteriological sample submitted to Department mitted  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below taken supply 1 and the surface 12 in., weight 2.9  YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 2 Louvered shutter 4 Key punched 7 Torch cut 1 CREEN-PERFORATED INTERVALS: From 100 ft. to 160 ft., From ft. to ft., From ft.	Application Number:  VATION:  t. 2. ft. 6 surface measured on mo/day/yr after hours put after	
DEPTH OF COMPLETED WELL 1.60 ft. ELE  NA Pump test data: Well water was  Est. Yield gpm: Well water was  Est. Yield gpm: Well water was  Est. Yield gpm: Well water was  Bore Hole Diameter 9 in to 160  WELL WATER TO BE USED AS: 5 Public water supply  Domestic 3 Feedlot 6 Oil field water supply  2 Irrigation 4 Industrial 7 Lawn and garden on  Was a chemical/bacteriological sample submitted to Department  mitted  TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile  1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify because)  2 PVC 4 ABS 7 Fiberglass  Jank casing diameter 5 in to 140 ft., Dia in to  Jassing height above land surface 12 in, weight 2.9  YPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)  2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS  CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped  1 Continuous slot 3 Mill slot 6 Wire wrapped  2 Louvered shutter 4 Key punched 7 Torch cut  CREEN-PERFORATED INTERVALS: From 1.00 ft. to 1.60 ft.,  From	VATION:  t. 2	
WELL'S STATIC WATER LEVEL . 129	surface measured on mo/day/yr after hours put after hours put after hours put after hours put and in 8 Air conditioning 11 9 Dewatering 12 7 10 Observation well Yes	umping gpm umping gpm n. to ft. Injection well Other (Specify below) s, mo/day/yr sample was sub
GCREEN-PERFORATED INTERVALS:         From.         140         ft. to         160         ft.,           From.         ft.         to <t< td=""><td>10 Asbestos-cem 11 Other (specify 12 None used (op 8 Saw cut) 9 Drilled holes</td><td>No. •<b>265</b> ent )</td></t<>	10 Asbestos-cem 11 Other (specify 12 None used (op 8 Saw cut) 9 Drilled holes	No. • <b>265</b> ent )
CREEN-PERFORATED INTERVALS:         From.         140         ft. to         160         ft., to           From.         ft. to         ft. to         ft., to         ft., to         ft., to           GROUT MATERIAL:         1 Neat cement         2 Cement grout         3 Bentonite	9 Drilled holes	
From.   ft. to   ft.,   GRAVEL PACK INTERVALS:   From.   100   ft. to   160   ft.,		
	From ft.	to
would intervals. From		
that is the nearest source of possible contamination:		Abandoned water well
	•	Other (specify below)
		· · · · · · · · · · · · · · · · · · ·
	many feet? 75	
FROM TO LITHOLOGIC LOG FROM TO	LITHOLOG	3IC LOG
6 29 Clay 29 35	Sand comented	
35 40 Clay 40 67	Sandy clay	
67 71 Clay 71 84	Sand comented	
84 95 Fine sand with clay streaks 95 104	Clay	
104 110 Fine sand with clay streaks 110 120	Fine sand	
120 130 Sand 130 140	Fine sand	
140 157 Sand 157 160	Yellow clay	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) completed on (mo/day/year)	econstructed, or (3) plugged un-	der my jurisdiction and was
Vater Well Contractor's License No		J