


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 17	Township Number T 18 S	Range Number R 36 EW																																																												
Distance and direction from nearest town or city street address of well if located within city?																																																																	
From Leoti: 1 1/2 E.																																																																	
2 WATER WELL OWNER:		ESE Alcohol																																																															
RR#, St. Address, Box #:		P.O. Box 813																																																															
City, State, ZIP Code:		Leoti, KS 67861																																																															
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:																																																																	
		4 DEPTH OF COMPLETED WELL 172 ft. ELEVATION : Depth(s) Groundwater Encountered 1...139 ft. 2... ft. 3... ft. WELL'S STATIC WATER LEVEL 139 ft. below land surface measured on mo/day/yr Pump test data: Well water was 165 ft. after 2 hours pumping 102 gpm Est. Yield 102 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 36 in. to 172 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes...No...X... If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No																																																															
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing joints: Glued ... Clamped ... 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded ... X... Blank casing diameter 16 in. to 172 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 24 in., weight lbs./ft. Wall thickness or gauge No.																																																																	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)																																																																	
SCREEN-PERFORATED INTERVALS: From 162 ft. to 152 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 172 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft.																																																																	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Existing Wells																																																																	
Direction from well?																																																																	
<table border="1"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> </tr> </thead> <tbody> <tr><td>0</td><td>2</td><td>Top Soil</td></tr> <tr><td>2</td><td>21</td><td>Sandy Clay</td></tr> <tr><td>21</td><td>33</td><td>Caliche</td></tr> <tr><td>33</td><td>53</td><td>Fine to Coarse Sand, Tight Limestone</td></tr> <tr><td>53</td><td>61</td><td>Limestone</td></tr> <tr><td>61</td><td>78</td><td>Fine to Coarse Sand</td></tr> <tr><td>78</td><td>92</td><td>Pea Gravel with Limestone</td></tr> <tr><td>92</td><td>97</td><td>Tan Clay</td></tr> <tr><td>97</td><td>118</td><td>Coarse Sand</td></tr> <tr><td>118</td><td>120</td><td>Tan Clay</td></tr> <tr><td>120</td><td>128</td><td>Fine to Coarse Sand, Loose</td></tr> <tr><td>128</td><td>130</td><td>Tan Clay</td></tr> <tr><td>130</td><td>139</td><td>Fine to Coarse Sand, Loose</td></tr> <tr><td>139</td><td>141</td><td>Clay</td></tr> <tr><td>141</td><td>162</td><td>Coarse Sand, Small Gravel, loose</td></tr> </tbody> </table>			FROM	TO	LITHOLOGIC LOG	0	2	Top Soil	2	21	Sandy Clay	21	33	Caliche	33	53	Fine to Coarse Sand, Tight Limestone	53	61	Limestone	61	78	Fine to Coarse Sand	78	92	Pea Gravel with Limestone	92	97	Tan Clay	97	118	Coarse Sand	118	120	Tan Clay	120	128	Fine to Coarse Sand, Loose	128	130	Tan Clay	130	139	Fine to Coarse Sand, Loose	139	141	Clay	141	162	Coarse Sand, Small Gravel, loose	<table border="1"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>PERFORATING INTERVALS</th> </tr> </thead> <tbody> <tr><td>162</td><td>163</td><td>Yellow Clay</td></tr> <tr><td>163</td><td>180</td><td>Blue Shale</td></tr> <tr><td>180</td><td></td><td>Total Depth</td></tr> </tbody> </table>			FROM	TO	PERFORATING INTERVALS	162	163	Yellow Clay	163	180	Blue Shale	180		Total Depth
FROM	TO	LITHOLOGIC LOG																																																															
0	2	Top Soil																																																															
2	21	Sandy Clay																																																															
21	33	Caliche																																																															
33	53	Fine to Coarse Sand, Tight Limestone																																																															
53	61	Limestone																																																															
61	78	Fine to Coarse Sand																																																															
78	92	Pea Gravel with Limestone																																																															
92	97	Tan Clay																																																															
97	118	Coarse Sand																																																															
118	120	Tan Clay																																																															
120	128	Fine to Coarse Sand, Loose																																																															
128	130	Tan Clay																																																															
130	139	Fine to Coarse Sand, Loose																																																															
139	141	Clay																																																															
141	162	Coarse Sand, Small Gravel, loose																																																															
FROM	TO	PERFORATING INTERVALS																																																															
162	163	Yellow Clay																																																															
163	180	Blue Shale																																																															
180		Total Depth																																																															
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07-01-91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KS.514 This Water Well Record was completed on (mo/day/yr) 07-08-91 under the business name of Miller Gearhead & Pump Repair, Inc. by (signature) <i>Edmund Miller</i>																																																																	
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																																																	