WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Location of well: | County | Fraction | | Section number | | Township number | Range number | | |
|--------------------------------------------------------------------------------------------|----------|-----------------|-----|----------------------------------------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------|--|
| | Whichita | SW 1/4 SW 1/46W | 1/4 | | 8 | т 18 s | R 37 | E/W | |
| 2. Distance and direction from nearest town or city: I miles west 1 mile north of Leota | | | | 3. Owner of wellen Ho lland R.R. or street: Box 264 City, state, zip code: Leoti, Ks 67861 | | | | | |
| 4. Locate with "X" in section below: N | | | | | | 6. Bore hole dia. 21 in. Completion date 4=1478 Well depth 211 ft. | | | |
| ₩ | | | | | | 7Cable tool X_ RotaryDrivenDugHollow rodJettedBoredReverse rotary 8. Use:DomesticPublic supplyIndustry XIrrigationAir conditioningStockLawnOil field waterOther | | | |
| SW SE | | | | | | 9. Casing: Material Steel Height: Lovy or below Threaded Welded Surface 12 in . RMP PVC Weight lbs./ft. Dia. 16 in to 211 ft. depth Wall Thickness: inches or | | | |
| 5. Type and color of material | | | | From | То | Dia in. to ft. depth gage No | | | |
| Clay Gyp | | | | 20 | 20 60 | Inakewood Iype Millslot Dia. 16" Star gauze 1/8 x 2 Length 60' | | | |
| Gyp, Sand | | | | 60 | 80 | Set between 151ft. andftft. andft. Gravel pack? YES Size range of material 1 x 1. | | | |
| Dirty Sand | | | | 80 | 100 | 11. Static water level: mo./day/yr. | | | |
| Sandy Clay | | | | 100 | | 12. Pumping level below land surfaces: 207 ft. after3 hrs. pumping675g.p.m. | | | |
| Med. to fime sand | | | | 120 | 140 | ft. after hrs. pumpingg.p.m. Estimated maximum yield675g.p.m. | | | |
| Med to coarse gravel, little clay | | | | 11,0 | 160 | 13. Water sample submitted: mo./day/yr. Yes No Date | | | |
| Loose gravel | | | | 160 | 180 | 14. Well head completion: | | | |
| Loose gravel, rokk | | | | 180 | 195 | Pitless adapter 12 Inches above grade 15. Well grouted? <u>Ves</u> | | | |
| Brown clay, shale at 200 | | | | 195 | 211 | With: Neat cement Bentonite _X Concrete Depth: From ft. to ft. | | | |
| | | | | | | 16. Nearest source of possible ft Direction Well disinfected upon comple | Туре | IA V No V | |
| | | | | | | 17. Pump: Manufacturer's name B & | Not installed | - W | |
| | | | | | | Model number Imknown Length of drop pipe 200 | | | |
| | | | | | | Type: Submersible | Turbine | | |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | Recipro | ocating S | |
| 19. Remarks: Used pump (his) | | | | | | 20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Drilling supply Inc. 136A Business 1002 N 3rd, GArden City, Ks Signed Report Report Date 5-10-8 | | | |