USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

SHARON SPRINGS 45W

WATER WELL RECORD

KSA 82a-1201-1215

DAN

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)
Topeka, Kansas 66620

		- '^(,')					peka, Kansas 0002U	
1. Location of well:	County	County Fraction			number	Township number Range number		
	Greeley	SE 1/4SW 1/4 NW	1/4	7		т 18	s R 39	€ Ø
2. Distance and direction from nearest town or city: $4N$, $\frac{1}{4}E$, $\frac{1}{2}S$ of 3.					:	Robt. Brunswig		
Street address of well	1	r street: tate - zin c	oda:	Tribune, KS 6	7879			
4. Locate with "X" in section below: Sketch map:				City, state, zip code:		6. Bore hole dia. 24 in. Completion date		
, N				e en		Well depth 151 ft. 6-13-77		
1 1		FEEDLOT	ļ .			7 Cable tool Rotar	y Driven Dug d Bored _ X Rever	en roterne
- NW	NE	\wedge			•	8. Use: Domestic		
# W X	E	1/1/2	. .`			X Irrigation	Air conditioning Sto	ck
sw	SE	1 /2	· // ·			9. Casing: Material Ste	Oil field water Otl	
<u> </u>	i	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			2	Threaded Welded	X_Surface10	in-
S 1 ★ 1 Mi		X WELL	May 14 Tribus	# .j ' ; '		RMP	Weight 17.5	_lbs./ft. hes or
5. Type and color of material					То	Dia in. to ft. de		
-			· · · ·	+			ohn son	
Clay				0	19	Type Galv. Steel		
Gyp				19	49	Slot auze 100 Set between 131	Length	<u>ft.</u>
Cla	v			49	58	Gravel pack 3Ves Size	and5/8-	1/4"
Sd rock H				58	60	11. Static water level:mo./day/yr.		
Clay				60	71	11.5 ft. below land s	nd surfaces:	
					92	140 ft. after 8 hrs. pumping 100g.p.m.		
Sdy clay				71	72	Estimated maximum yield 180 g.p.m.		
Sd 'coarse'				92	101	13. Water sample submitted: mo./day/yr. Yes X No Date		
Clay				101	108	14. Well head completion:		
Sd 'med'				108	110	Pitless adapter Inches above grade		
Clay				110	115	15. Well grouted? <u>YES</u> With: <u>X</u> Neat cement Bentonite Concrete Depth: From ft. to ft.		
Fine sd clay				115	———————————————————————————————————————	Depth: From ft. to ft. 16. Negrest source of possible contamination: Feed ft. 2640 Direction North Type Lot		
Sd coarse				130	135			
						17. Pump:	Not installed	,
Clay				135	140	Manufacturer's name G Model number Uh66LM	34 HP 10 Volt	<u>,460</u>
Sd coarse				140	142	Length of drop pipe	L ft. capacity 180	g.p.m.
Clay yellow				142	153	Type: X Submersible	Turbine	
Shale (Use a second sheet if needed)				153	155	Jet Centrifugal	Recipro	cating (
18. Elevation:	19. Remarks:	OCK 142'		· · · · ·	-	20. Water well contractor! This well was drilled under	· · · · · - · · ,	
						is true to the best of my kn	owledge and belief.	`
Topography: HIII 35(0) (TUTC)						Weishaar Dr Business name		232 Inse No.
X Slope	2740	· · · · · · · · · · · · · · · · · · ·				Add South	KS 67871	3
Upland Valley					9	Service of the servic	ep/esentative 7 - 12	77
	ue and pink copies to the Departm	nent of Health and Environment			<u>-</u>		Form WV	 C-5