

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Greeley</u>	<u>NW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	<u>17</u>	T <u>18</u> S	R <u>39</u> EW

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: <u>Pringle Ranch Co Pringle, Coler</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>R.R.</u>	Application Number:
City, State, ZIP Code: <u>Tribune, KS 67879</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>102'</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: <u>85'</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield: <u>10</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic (circled) 3 Feedlot 6 Oil field water supply 9 Dewatering (12) Other (Specify below) <u>Pasture Well</u> 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was sub- mitted Water Well Disinfected? Yes No <u>X</u>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: <u>Glued</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC (circled)	4 ABS	7 Fiberglass	<u>Welded</u> <u>Threaded</u> (circled)
Blank casing diameter: <u>5</u> in. to <u>82</u> ft., Dia			
Casing height above land surface: <u>12"</u> in., weight			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC (circled)	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut (circled)	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>102'</u> ft. to <u>82</u> ft., From		
	From	ft. to	ft., From
GRAVEL PACK INTERVALS:	From <u>102'</u> ft. to <u>20'</u> ft., From		
	From	ft. to	ft., From

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite (circled)	4 Other
Grout Intervals:	From <u>0</u> ft. to <u>20</u> ft., From			
	From	ft. to	ft., From	ft. to
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below) <u>NONE</u>

Direction from well?		How many feet?	
FROM	TO	LITHOLOGIC LOG	PLUGGING INTERVALS
0	20	Overburden: Clay	
20	40	Sand: Clay Strips	
40	60	Sand: Clay Strips	
60	80	Sand	
80	97	Sand	
97	102	Blue Shale	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>May 23, 1992</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>K-300</u> This Water Well Record was completed on (mo/day/yr) <u>May 23, 1992</u> under the business name of <u>Fulter Drilling Co.</u> by (signature) <u>[Signature]</u>
--