

1 LOCATION OF WATER WELL: County: Greeley	Fraction SW ¼ NW ¼ SW ¼	Section Number 3	Township Number T 18 S	Range Number R 40 E (W)
---	---	----------------------------	----------------------------------	--

Distance and direction from nearest town or city street address of well if located within city?

2 miles north, 1 mile east of Tribune, KS

2 WATER WELL OWNER: City of Tribune	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : City, State, ZIP Code : Tribune, KS 67879	Application Number: none

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 181 ft. ELEVATION: 3620
	Depth(s) Groundwater Encountered 1. 130 ft. 2. 130 ft. 3. 130 ft.
	WELL'S STATIC WATER LEVEL 130 ft. below land surface measured on mo/day/yr 2-8-90
	Pump test data: Well water was 130 ft. after 5 1/2 hours pumping 181 gpm
	Est. Yield 181 gpm: Well water was 130 ft. after 5 1/2 hours pumping 181 gpm
	Bore Hole Diameter 6 1/4 in. to 23 ft., and 5 1/2 in. to 181 ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well test well	
Was a chemical/bacteriological sample submitted to Department? Yes X No _____ ; If yes, mo/day/yr sample was submitted 2-9-90	
Water Well Disinfected? Yes X No _____	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped _____
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded _____
Blank casing diameter 3 in. to 161 ft., Dia 161 in. to 161 ft., Dia 161 in. to 161 ft.			Threaded _____
Casing height above land surface 24 in., weight 24 lbs./ft. Wall thickness or gauge No. Sch 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
			9 ABS
			10 Asbestos-cement
			11 Other (specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	11 None (open hole)
		7 Torch cut	9 Drilled holes
			10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 161 ft. to 181 ft., From 161 ft. to 181 ft., From 161 ft. to 181 ft.			
GRAVEL PACK INTERVALS: From 20 ft. to 181 ft., From 20 ft. to 181 ft., From 20 ft. to 181 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 181 ft., From 181 ft. to 181 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	
Direction from well? south			How many feet? 990	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	16	top soil & limestone			
16	33	limestone & 2' clay & little sand			
33	49	cemented sand & limestone & little clay			
49	66	sandy clay & limestone			
66	88	limestone & sand			
88	91	clay			
91	115	sandy clay			
115	132	sand & sandy clay streaks			
132	143	sand (medium to coarse)			
143	145	cemented sand & clay & limestone (hard)			
145	149	sand (medium to coarse)			
149	161	sandy clay & 3' sand			
161	166	sand (medium to coarse) 1' clay			
166	173	clay			
173	181	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-9-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/yr) 2-11-90 under the business name of XXXXX Tyler Water Well Service by (signature) Pat L. Lyle
