

1 LOCATION OF WATER WELL: County: Greeley	Fraction SE ¼    SE ¼    NE ¼	Section Number 24	Township Number T 18 S	Range Number R 41 EW
--	----------------------------------	----------------------	---------------------------	-------------------------

Distance and direction from nearest town or city street address of well if located within city?  
1/4 East of Horace

2 WATER WELL OWNER: Dave Woelk  
RR#, St. Address, Box # :  
City, State, ZIP Code : Tribune Ks  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
4 DEPTH OF COMPLETED WELL: 127 ft. ELEVATION: 3620

Depth(s) Groundwater Encountered 1. 100 ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL 100 ft. below land surface measured on mo/day/yr 5-1-97  
Pump test data: Well water was 120 ft. after 1 hours pumping 10 gpm  
Est. Yield 10 gpm: Well water was ft. after hours pumping gpm  
Bore Hole Diameter 10 in. to ft. and in. to ft.  
WELL WATER TO BE USED AS:  
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well  
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
7 Fiberglass Threaded  
Blank casing diameter 5 in. to 107 ft. Dia. in. to ft. Dia. in. to ft.  
Casing height above land surface 24 in. weight lbs./ft. Wall thickness or gauge No. Sch 40  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 107 ft. to 127 ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 80 ft. to 127 ft. From ft. to ft.  
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 70 ft. to 80 ft. From 10 ft. to 30 ft. From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? East How many feet? 200'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	13	Top soil and clay			
13	16	Sand			
16	32	Clay caliche and little sand			
32	43	Sand and gravel			
43	65	Clay and caliche			
65	82	Sandy clay			
82	98	Clay and little caliche			
98	109	Sand medium to coarse and little cemented sand			
109	114	Caliche			
114	124	Yellow clay			
124	127	Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/19/97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 473 This Water Well Record was completed on (mo/day/yr) 5/19/97 under the business name of Tyler Water Well Service Inc. by (signature) *Paul G...*

OFFICE USE ONLY  
T  
R  
EW  
SEC  
1/4  
1/4