

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>McPherson</u>	NW 1/4 NW 1/4 SW 1/4	22	T 19 S	R 1 E(W)

Distance and direction from nearest town or city street address of well if located within city?

209 S Main Street, Canton, Ks. MW 8

2 WATER WELL OWNER: <u>The Canton Elevator</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>209 S Main St.</u>	Application Number:
City, State, ZIP Code : <u>Canton, Kks. 67428</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>45</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>35</u> ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL <u>32.85</u> ft. below land surface measured on mo/day/yr <u>2-19-92</u>
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter <u>7 5/8</u> in. to <u>45</u> ft. and in. to ft.	
WELL WATER TO BE USED AS:	
1 Domestic	5 Public water supply
2 Irrigation	6 Oil field water supply
3 Feedlot	7 Lawn and garden only
4 Industrial	8 Air conditioning
	9 Dewatering
	10 Monitoring well
	11 Injection well
	12 Other (Specify below)
Was a chemical/bacteriological sample submitted to Department? Yes No ☒	If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No ☒	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>2</u> in. to <u>25</u> ft. Dia			Threaded ☒
Casing height above land surface <u>0</u> in., weight lbs./ft. Wall thickness or gauge No. <u>Schedule 40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS: From <u>25</u> ft. to <u>45</u> ft.			
GRAVEL PACK INTERVALS: From <u>23</u> ft. to <u>45</u> ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS: From <u>0</u> ft. to <u>19</u> (cement) ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>Northwest</u>			13 Insecticide storage	
			How many feet? <u>150</u>	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	Clay, black			
1.5	11	Silty clay, reddish brown			
11	21.5	Sandy clay, reddish brown			Flush Mount Cover
21.5	26	Silty sand, reddish brown			KDHE Site ID# 00099260
26	31	Sand, reddish brown, fine			
31	36.5	Silty sand, grey			
36.5	45	Sand, grey, fine			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>2-15-92</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>527</u> This Water Well Record was completed on (mo/day/yr) <u>2-26-92</u> under the business name of <u>GeoCore Services, Inc.</u> by (signature) <u>Dale A. Bly</u>
