

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>McPherson</u>	NW 1/4 NW 1/4 SW 1/4	<u>30</u>	T <u>19</u> S	R <u>1</u> W

Distance and direction from nearest town or city street address of well if located within city?

3 miles West & 3/4 mile South of Canton, KS2 WATER WELL OWNER: Chester SchmidtRR#, St. Address, Box #: RR 2

Board of Agriculture, Division of Water Resources

City, State, ZIP Code: Galva, KS 67443Application Number: T87-314

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 55 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 22 ft. 2. 22 ft. 3. 8/17/87 ft.WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yrPump test data: Well water was 30-40 gpm: Well water was 55 ft. after 8 hours pumping 17 gpmEst. Yield 30-40 gpm: Well water was 55 ft. after 8 hours pumping 17 gpmBore Hole Diameter 6 in. to 55 ft., and 55 in. to 55 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)

2 PVC 4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued ClampedWeldedThreadedBlank casing diameter 3 in. to 35 ft., Dia 1.50 in. to 1.65 in. to 1.65 in. to 1.65 in.Casing height above land surface 12 in., weight 1.50 lbs./ft. Wall thickness or gauge No. 165

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel

2 Brass 4 Galvanized steel

5 Fiberglass

6 Concrete tile

7 PVC

8 RMP (SR)

9 ABS

10 Asbestos-cement

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

2 Louvered shutter

4 Key punched

5 Gauzed wrapped

6 Wire wrapped

7 Torch cut

8 Saw cut

9 Drilled holes

10 Other (specify)

11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 35 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.GRAVEL PACK INTERVALS: From 20 ft. to 55 ft., From 55 ft. to 55 ft.7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-17-87 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 8-18-87under the business name of Peterson Irrigation, Inc. by (signature) Mike Peterson

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.