WATER	WELL RE	CORD	Form W	WC-5	Division of Wat	er Resources App. No	0.	
1 LOCA	ATION OF WA	TER WELL:	Fraction		Section Number	Township No.	Range Number	
Count	y: McPh	erson	1/4 Ne 1/4 Ne	2 1/4 N C 1/4	21	T 19 S	R / DE ZW	
			if unknown, distance a			g System (GPS) in		
from r	learest town or	intersection: If at	owner's address, chec	Latitude:				
					Datum: WGS 8	84, □ NAD 83, □	NAD 27	
2 WATER WELL OWNER: Pat John Son RR#, Street Address, Box #: 400 N Main					Collection Method:			
City, State, ZIP Code : 400 N Main					☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
Canton, Lobor 1928					Est. Accuracy: \bigcirc <3 m, \bigcirc 3-5 m, \bigcirc 5-15 m, \bigcirc >15 m			
3 LOCATE WELL								
WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL								
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3) ft.								
WELL'S STATIC WATER LEVEL								
	The rest of the re							
W - NW - NE - EST. YIELD . Well water was								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SWSE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
Irrigation Industrial Domestic-lawn & garden Monitoring well Irrigation								
Was a chemical/bacteriological sample submitted to Department? Yes No								
S If yes, mo/day/yr sample was submitted Water well disinfected? Yes No								
water werr districted: Fires								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Deflued Clamped Welded Threaded Casing diameter in. to fin., Diameter in. to fin., Diameter in. to fin., Diameter in., to fin., Diameter in., to fin., Diameter in., to fin., Wall thickness or gauge No. 214.								
Casing height above land surface. 2 in. Weight SDR26 lbs/ft Wall thickness or gauge No 2/4								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE: Continuous slot Mill slot Gauze wrapped Torch out Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut O Tother (specify)								
SCREEN-PERFORATED INTERVALS: From. L. ft. to								
From								
From ft. to ft., From ft. to ft. 6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From C ft. to SC ft., From ft. to ft., From ft. to ft.								
What is the nearest source of possible contamination:								
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below)								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
	ion from well.		pit Li reedyaid	leanne.	from well <i>J.D</i>			
FROM	TO TO	LITHOLOG		FROM	······································		IGGING INTERVALS	
		110W Cla				en e		
	,					(D)	Color IV (for tax)	
35	45 41	ne San				II hass	North W. Born bed	
45	72 YE	llow Cla	X				v a M man	
~ 4	O n	/				NO	V 27 2012	
72	Pl me	d Sound				OT ICA-	NU OF WATER	
DO	90 131	ve Shal				LJUTTL-/	Now to a series	
J J	70 11	e July	C					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged								
under my jurisdiction and was completed on (mo/day/year) 9-26-12 and this record is true to the best of my knowledge and belief.								
under my jurisdiction and was completed on (mo/day/year) ?								
under the business name of								
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PREST</u> clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.								
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212								