WATE	R WELI	L RECORD	Form WWC-	·5	Division of Wate	Division of Water Resources; App. No.		
			Fraction		Section Number	, .	Range Number	
			NW 1/4 SE 1/4		3	T 19 S	R 10 XEXW	
	Distance and direction from nearest town or city street address of well if Global Positioning Systems (decimal degrees, min. of 4 digits							
						Latitude:		
2 WA	3 West, 4½ North of Chase 2 WATER WELL OWNER: Darrel Hoelscher					Longitude:		
1	2 WATER WELL OWNER: Darrel Hoelscher RR#, St. Address, Box # : 502 S. 1st St				Elevation:			
i .	, St. Addit , State, ZII	502 51 100			Datum:			
		Basileeri, 10		17	Data Collection	Method:		
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL								
1	A HON H AN "X'	IN Denth(s) Groundwater	Encountered (1)		ft (2)	ft (3)	A	
1	THAN "X" IN Depth(s) Groundwater Encountered (1)							
220	N	N Pump test data: Well water was						
<del> </del>	Est. Yield. N/Agpm: Well water wasft. after hours pumping							
l l NN	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
w								
	2 Irrigation 4 Industrial 7—Domestic (lawn & garden)—10 Monitoring well							
SV	V   SE	1	1 1 1		D 4 40 TV	X	TO /1 /	
	*	Was a chemical/bacteri Sample was submitted.	ological sample subn	nitted to	Department? Yes.	; No;	If yes, mo/day/yrs	
	c	Sample was submitted.		. wate	er well disinfected?	Yes No	•••	
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: GluedX Clamped								
1		$\mathcal{Q}$	ron 8 Conc	rete tile	CASING	G JOINTS: GluedX		
1	Steel PVC	3 RMP (SR) 6 Asbestos-6 4 ABS 7 Fiberglass	Cement 9 Otner	(specify	below)	weided Threaded		
Blank casing diameter5 in. to97 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface24 in., WeightSDR=26lbs./ft. Wall thickness or guage No								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
GRAVEL PACK INTERVALS: From								
From34								
Troni								
		ERIAL: 1 Neat cement 2 C	Cement grout 3 Ber	ntonite	4 OtherHole	plug		
Grout Intervals: From								
What is the nearest source of possible contamination:								
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well _below)								
1		sewer lines 6 Seepage pit				well/gas well	.below) House	
Direction from well? North How many feet? 100								
FROM	TO	LITHOLOGIC		FROM		PLUGGING INTE		
0	28	Clay with some fine	******			120001101111	310,1120	
28	32	Sandstone						
32	37	Clay						
37	48	Sandstone with clay	streaks					
48	115	Hard sandstoneX						
115	117							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year) 1-22-09 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No								
under the business name of ROSENCRANTZ- BEMLS by (signature) Source of the correct answers. Send top INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top								
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone								
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								

KSA 82a-1212