		LL RECORD	Form W	/WC-5	Division of Wate	er Resources App. N	o.
	CATION inty: Ric	N OF WATER WELL:	Fraction 1/4 SW 1/4 SE	- 4 SF 4	Section Number		Range Number R 10
		Address of Well Location;			Global Positioning System (GPS) information:		
		town or intersection: If at		Latitude:			
		, 4 3/4 West of Chase	,	Longitude:			
,					Elevation:		
2 WATER WELL OWNER: Mitchell Haddon					Datum: WGS 84, NAD 83, NAD 27		
		WILCONON	Haddon		Collection Method:		
RR#, Street Address, Box #: 237 SE 30 Road City, State, ZIP Code : Croet Bond No. 67530				☐ GPS unit (Make/Model:) ☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey			
	,, ~	. Great B	end, Ks. 67530		Est. Accuracy:	3 m. \square 3-5 m. \square	5-15 m \square >15 m
	CATE WI	ELL	, <u>, , , , , , , , , , , , , , , , , , </u>				<u> </u>
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 60 ft.							
SECTION BOX: Depth(s) Groundwater Encountered (1)							
,	18	WELL'S STATI	C WATER LEVEL	?ft.	below land surface	measured on mo/da	ay/yr5-24-11
	1	Pump	test data: Well water	er was	ft. after	hours pump	oing gpm
	W N	EST. YIELD	gpm. Well wate	er was	ft. after	hours pum	ping gpm
W E Bore Hole Diameter 10							
This state of the							
L			hacteriological sample	e submitted to	Department?	Voc 17 No	·····
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
1 mile Water well disinfected?							
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other							
Casing diameter 5 in to 60 ft Diameter in to 6 Pierreter in to 6							
Casing diameter .5							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify)							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)							
☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify) SCREEN-PERFORATED INTERVALS: From60							
From fit to fit from fit f							
GRAVEL PACK INTERVALS: From 60 ft. to 20 ft., From ft. to ft.							
From							
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From ft. to ft., From 20 ft., From ft., From ft. to ft.							
Grout Intervals: From ft. to ft., From .20 ft., From ft., From ft. to ft.							
what is the nearest source of possible contamination:							
	Septic tar Sewer lin			Livestock pe			r (specify below)
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well ☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None							
Direc	ction fron	n well	i i recuyaru j			· ·····	
FROM	TO	LITHOLOGI	C LOG		TO LITHO LC	G (cont.) or PLUC	GGING INTERVALS
)	3	Top soil			TO BITTO: EC	o (com.) or 1 bec	DOMO INTERVALS
3	27	Sandy clay					
27	34	Sandy clay & fine sand					
34	55	Sand & gravel- small, co	arse				
55	60	Gray shale					
							The state of the s
	TD / 677	DIC ON T					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ✓ constructed, ☐ reconstructed, or ☐ plugged							
under my jurisdiction and was completed on (mo/day/year) 2-24-11 and this record is true to the best of my knowledge and belief							
Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/year) 6-2-11.							
under the business name of Rosencrantz- Bemis by (signature) Source Send three copies INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
Wille, blue, plik) to Kansas Department of Health and Environment Bureau of Water Geology Section 1000 SW Joseph 420 Tanaly 10 research 1000 SW Joseph							
cicphone	103-290-3	322. Send one copy to WATE	R WELL OWNER and re	tain one for you	ir records. Include fee	of \$5.00 for each con	istructed well. Visit us at
LLD.// WWW	Kulleks.gu	v/waterwell/index.html.		-			
SA 82a-1212 Check: X White Copy, D Blue Copy, Pink Copy							