


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BARTON		NE 1/4 NW 1/4 SE 1/4	31	T 19 S	R 11 E/W
Distance and direction from nearest town or city street address of well if located within city? 307 E. SANTA FE ELLINWOOD, KS PW					
2 WATER WELL OWNER: GARVEY GRAIN INC		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: BOX 12560		Application Number:			
City, State, ZIP Code: WICHITA, KS 67277					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1785.04			
		Depth(s) Groundwater Encountered 1. 13.5 ft. 2. . ft. 3. . ft.			
		WELL'S STATIC WATER LEVEL . ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was . ft. after . hours pumping . gpm			
		Est. Yield . gpm; Well water was . ft. after . hours pumping . gpm			
Bore Hole Diameter: 14 in. to . ft., and . in. to . ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	PUMP TEST
Was a chemical/bacteriological sample submitted to Department? Yes. . No. X .; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes . No X .			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued . Clamped .
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded .
Blank casing diameter: 5 in. to . ft., Dia . in. to . ft., Dia . in. to . ft.		7 Fiberglass	Threaded .		
Casing height above land surface: FLUSH in., weight 2.00 lbs./ft. Wall thickness or gauge No. .250		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify) .
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify) .	
SCREEN-PERFORATED INTERVALS: From 10 ft. to 20 ft., From . ft. to . ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 30 ft., From . ft. to . ft.					
6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other .
Grout Intervals: From 2 ft. to 8 ft., From . ft. to . ft.					
What is the nearest source of possible contamination:		10 Livestock pens	14 Abandoned water well		
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? 0000 EAST		How many feet? 70'			
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	10	FILL, GRAVEL, LEAN CLAY			
		ALLUVIUM, MINOR SAND			
10	20	FINE GRAINED, POOR GRADED SAND			
20	30	FINE TO COARSE, WELL GRADED SAND, POOR GRADED SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-19-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 10-31-95 under the business name of GSI by (signature) Matt Wolf					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4