

1 LOCATION OF WATER WELL: County: BARTON		Fraction SW 1/4 NE 1/4 SE 1/4	Section Number 31	Township Number T 19 S	Range Number R 11 E/W
Distance and direction from nearest town or city street address of well if located within city? 501 E. SANTE FE ELLIWOOD					
2 WATER WELL OWNER: RR#, St. Address, Box # LEBBIN OIL & PROpane CO City, State, ZIP Code 501 E. SANTE FE- ELLIWOOD, KS. 67526					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 12 ft. 2. — ft. 3. — ft.			
		WELL'S STATIC WATER LEVEL 17.59 ft. below land surface measured on mo/day/yr 06-28-94			
		Pump test data: Well water was — ft. after — hours pumping — gpm			
		Est. Yield — gpm Well water was — ft. after — hours pumping — gpm			
Bore Hole Diameter 8.625 in. to 20 ft. and — in. to — ft.		WELL WATER TO BE USED AS:			
1 Domestic		3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation		4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes — No X If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes — No X					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded —
2 PVC		4 ABS	7 Fiberglass		Threaded X
Blank casing diameter 2 in. to 24 in. Dia 9.2 ft. Dia — in. to — ft. Dia — in. to — ft.					
Casing height above land surface 24 in. weight SCH 40 lbs./ft. Wall thickness or gauge No. —					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify) —
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter		4 Key punched	7 Torch cut	10 Other (specify) —	
SCREEN-PERFORATED INTERVALS: From 9.2 ft. to 19.2 ft. From — ft. to — ft.					
From — ft. to — ft. From — ft. to — ft.					
GRAVEL PACK INTERVALS: From 8 ft. to 20 ft. From — ft. to — ft.					
From — ft. to — ft. From — ft. to — ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From GL ft. to 6 ft. From 6 ft. to — ft. From — ft. to — ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
				13 Insecticide storage	CONTAMINATED SITE
Direction from well? — How many feet? —					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
GL	2	SOIL			
2	5	SILTY CLAY			
5	7	SANDY CLAY			
7	12	SAND			
12	17	SAND FINE			
17	20	SD-GRAVEL			
TD	20				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-28-94 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 07-15-94					
under the business name of EBERTS DRILLING by (signature) <i>Augan Eberts</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4