

1 LOCATION OF WATER WELL: County: BARTON		Fraction SW 1/4 NE 1/4 SE 1/4		Section Number 31		Township Number T 19 S		Range Number R 11 E/W			
Distance and direction from nearest town or city street address of well if located within city? W - N. WEILAND ST. N OF HWY 52 - ELLINWOOD											
2 WATER WELL OWNER: CITY OF ELLINWOOD											
RR#, St. Address, Box # ART. MEL. WAITE - 104 E 2ND - ELLINWOOD KS 67526						Board of Agriculture, Division of Water Resources					
City, State, ZIP Code						Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 20 ft. ELEVATION: 13.2 ft.								
			Depth(s) Groundwater Encountered 1. 13.2 ft. 2. — ft. 3. — ft.								
			WELL'S STATIC WATER LEVEL 12.85 ft. below land surface measured on mo/day/yr 06-28-94								
			Pump test data: Well water was — ft. after — hours pumping — gpm								
			Est. Yield — gpm. Well water was — ft. after — hours pumping — gpm								
			Bore Hole Diameter 8.625 in. to 20 ft. and — in. to — ft.								
			WELL WATER TO BE USED AS:								
			5 Public water supply		8 Air conditioning		11 Injection well				
			1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering		
			2 Irrigation		4 Industrial		7 Lawn and garden only		10 Monitoring well		
			Was a chemical/bacteriological sample submitted to Department? Yes — No X ; If yes, mo/day/yr sample was submitted —								
			Water Well Disinfected? Yes — No X								
5 TYPE OF BLANK CASING USED:											
1 Steel			3 RMP (SR)			5 Wrought iron			8 Concrete tile		
2 PVC			4 ABS			6 Asbestos-Cement			9 Other (specify below)		
			7 Fiberglass						CASING JOINTS: Glued — Clamped —		
									Welded —		
									Threaded X		
Blank casing diameter 2 in. to 9.1 ft. Dia — in. to — ft. Dia — in. to — ft.											
Casing height above land surface FLUSH in., weight SCH 40 lbs./ft. Wall thickness or gauge No. —											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel			3 Stainless steel			5 Fiberglass			7 PVC		
2 Brass			4 Galvanized steel			6 Concrete tile			8 RMP (SR)		
									10 Asbestos-cement		
									11 Other (specify) —		
									12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot			3 Mill slot			5 Gauzed wrapped			8 Saw cut		
2 Louvered shutter			4 Key punched			6 Wire wrapped			9 Drilled holes		
						7 Torch cut			10 Other (specify) —		
									11 None (open hole)		
SCREEN-PERFORATED INTERVALS:			From 9.1 ft. to 19.1 ft.			From — ft. to — ft.			From — ft. to — ft.		
			From 8 ft. to 20 ft.			From — ft. to — ft.			From — ft. to — ft.		
GRAVEL PACK INTERVALS:			From — ft. to — ft.			From — ft. to — ft.			From — ft. to — ft.		
			From — ft. to — ft.			From — ft. to — ft.			From — ft. to — ft.		
6 GROUT MATERIAL: 2 GL 1 Neat cement											
Grout Intervals: From GL ft. to 6 ft. From 3 ft. to 6 ft. From 8 ft. to — ft.											
What is the nearest source of possible contamination:											
1 Septic tank			4 Lateral lines			7 Pit privy			10 Livestock pens		
2 Sewer lines			5 Cess pool			8 Sewage lagoon			11 Fuel storage		
3 Watertight sewer lines			6 Seepage pit			9 Feedyard			12 Fertilizer storage		
									13 Insecticide storage		
									14 Abandoned water well		
									15 Oil well/Gas well		
									16 Other (specify below) CONTAMINATED SITE		
Direction from well? — How many feet? —											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
GL		1		SAND-GRAVEL							
1		4		SILTY CLAY							
4		10		SILTY CLAY GREEN-GRN							
10		20		SAND							
TD		20									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 06-28-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 07-15-94 under the business name of EBERTS DRILLING by (signature) <i>Erberts</i>											