

1 LOCATION OF WATER WELL: County: Barton		Fraction NW 1/4 NE 1/4 NE 1/4	Section Number 31	Township Number T 19 S	Range Number R 11
Distance and direction from nearest town or city street address of well if located within city? Located at 7th and Goethe St. Ellinwood, Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		City of Ellinwood, P.O. Box 278 Ellinwood, KS 67526			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 49 ft. ELEVATION: unknown			
		Depth(s) Groundwater Encountered 11 ft. 2. 11 ft. 3. 11 ft. WELL'S STATIC WATER LEVEL 11 ft. below land surface measured on mo/day/yr 7/15/86. Pump test data: Well water was not ckd. ft. after hours pumping gpm Est. Yield 450 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 30 in. to 47'6" ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes X No; If yes, mo/day/yr sample was submitted 6/20/86 Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded X 7 Fiberglass Threaded			
Blank casing diameter 12 3/4 in. to 31'2" ft., Dia in. to ft. Casing height above land surface 18 in., weight 43.77 lbs./ft. Wall thickness or gauge No. 330					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)		7 PVC 10 Asbestos-cement			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify) Johnson 100 slot			
SCREEN-PERFORATED INTERVALS: From 31'2" ft. to 47'6" ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 25 ft. to 47'6" ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? all		How many feet? over 50			
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG			
0 12 Topsoil & brown clay					
12 46 Sand & gravel, medium to fine to Coarse w/ thin clay streak @ 27' and very thin yellow clay stringers 30'-46'					
46 47'6" Brown clay					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/15/86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 7/18/86 under the business name of Clarke Well & Equipment, Inc. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					