


1 LOCATION OF WATER WELL: Fraction E 1/4 E 2 1/4 NE 1/4 Section Number 34 Township Number T 19 S Range Number R 11 E

County: BARTON

Distance and direction from nearest town or city street address of well if located within city?
ELLINWOOD 3E V4S WESTSIDE.

2 WATER WELL OWNER: L.D. DRILLING CO. INC. M. BRENN, ELLINWOOD, KS.
RR#, St. Address, Box #: RT 1 BOX 183B
City, State, ZIP Code: GREY BEND, KS 67530
Board of Agriculture, Division of Water Resources
Application Number: T83-554

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 1018.83
Depth(s) Groundwater Encountered 1. 13 ft. 2. 1018.83 ft. 3. 1018.83 ft.
WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 10-18-83
Pump test data: Well water was 13 ft. after 1018.83 hours pumping 1018.83 gpm
Est. Yield 13 gpm: Well water was 13 ft. after 1018.83 hours pumping 1018.83 gpm
Bore Hole Diameter 7 7/8 in. to 60 ft., and 60 in. to 60 ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes 13 No 1018.83; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes 13 No 1018.83

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued KK Clamped KK
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded KK
Blank casing diameter 5 in. to 40 ft., Dia 5 in. to 40 ft., Dia 5 in. to 40 ft.
Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. 214
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) KK
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 13 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) KK
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From 40 ft. to 60 ft., From 40 ft. to 60 ft.
GRAVEL PACK INTERVALS: From 13 ft. to 60 ft., From 13 ft. to 60 ft., From 13 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other KK
Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.
What is the nearest source of possible contamination: NONE 10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 5 Pit privy 11 Fuel storage 15 Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet?
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 13 CLAY FROM TO LITHOLOGIC LOG
13 57 GRAVEL FROM TO LITHOLOGIC LOG
57 60 CLAY FROM TO LITHOLOGIC LOG

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 10-26-83 under the business name of REISER WATER WELL SERV. INC. by (signature) Andreas J. Reiser
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.