

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BARTON		NE 1/4 NE 1/4 NE 1/4	36	T 19 S	R 11 E
Distance and direction from nearest town or city street address of well if located within city? 400 E 6th					
2 WATER WELL OWNER: Lloyd Wood					
RR#, St. Address, Box #: 400 E 6th					
City, State, ZIP Code: Ellinwood KS 67526					
Board of Agriculture, Division of Water Resources Application Number: NONE					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 6 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well ① Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... X If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel 2 PVC 3 RMP (SR) 1 1/2" ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded			
Blank casing diameter 1 1/2 in. to ft., Dia. in. to ft., Dia. in. to ft.		Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) NA 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) NA			
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft.		GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement ② Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 6 ft. to 3 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (Specify below) 21 RUNOFF 13 Insecticide storage					
Direction from well? SW		How many feet? 21 RUNOFF			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
15	6	CHLORINATED SAND			
6	3	CEMENT			
3	0	EARTH			
		1 1/2 HRS			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-5-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 9-5-90 under the business name of by (signature) Relly Starnes					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4