WATER WELL RECORD	Form WV	VC-5	Division of Wate	r Resources App. No),	
1 LOCATION OF WATER WELL: County: Barton	Fraction 1/4 NW 1/4 NW	1/4 NE 1/4	Section Number		Range Number R 11 □E ☑W	
Street/Rural Address of Well Location; if unknown, distance & direction		Global Positioning		formation:		
from nearest town or intersection: If at owner's address, check here		Latitude: (in decimal degrees)				
5E, 3N of Ellinwood, Ks		Longitude:				
2 WATER WELL OWNER: David and Pam Wirth			Datum: WGS 84, NAD 83, NAD 27			
2 WATER WELL OWNER: David and Pam Wirth RR#, Street Address, Box #: 673 NE 130 Ave.			Collection Method: GPS unit (Make/Model:)			
City, State, ZIP Code : Ellinwood, KS 67526		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOCATE WELL	Est. Accuracy: <	3 m, 3-5 m,	5-15 m,			
WITH AN "X" IN 4 DEPTH OF	COMPLETED WELL	, 65	ft.			
SECTION BOX: Depth(s) Ground	Depth(s) Groundwater Encountered (1).18 ft. (2)					
N WELL'S STAT	WELL'S STATIC WATER LEVEL. 18ft. below land surface measured on mo/day/yr. 11/7/14					
TOTAL TARREST CO	Pump test data: Well water was					
W - NW NE - EST. YIELD, 90	NE - EST. HELD 90gpin. Well water was					
WELL WATER	₩ELL WATER TO BE USED AS: Public water supply Geothermal Injection well					
Domestic	SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)					
│	Industrial Domestic-lawn & garden Monitoring well Stock					
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ✓ No If yes, mo/day/yr sample was submitted						
Water well disinfected?						
5 TYPE OF CASING USED: Steel PVC Other						
CASING JOINTS: V Glued Clamped Welded Threaded						
Casing diameter .5 in. to .45 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft.						
Casing height above land surface!						
TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel						
Brass Galvanized Steel None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☑ Saw cut ☐ Other (specify)						
SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft., From ft. to ft.						
From						
GRAVEL PACK INTERVALS: From						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other						
What is the nearest source of possible contamination:						
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)						
Sewer lines Cesspool Watertight sewer lines Seepage	Sewage lagoon [Dit Feedyard	Fuel storage Fertilizer st			- in field	
Direction from well			from well			
FROM TO LITHOLOG	FIC LOG	FROM	TO LITHO. L	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
0 2 top soil					No. Assessment Control of the Contro	
2 31 clay						
31 65 fine sand clay bottom						
Clay bottom						
				,		
					ALL CONTRACTOR OF THE CONTRACT	
					The state of the s	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☐ constructed, ☐ reconstructed, or ☐ plugged						
under my jurisdiction and was completed on (mo/day/year) .1.1/0.7/14 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/year) 11/9/14 under the business name of Kelly's Water Well Service, Inc. by (signature)						
under the business name ofKelly's Water	er vveli Service, Inc.	and DDINT -1	. by (signature)	and check the same	anguage Sand one comple	
INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.						
Telephone 785-296-5524. Send one copy to WAT	ER WELL OWNER and retai	n one for your	records. Include fee of \$	5.00 for each construc	ted well. Visit us at	

http://www.kdheks.gov/waterwell/index.html