KOLAR Document ID: 1536358

	WELL R	ECORD Correction		WWC-5 ge in Well Use		ivision of W sources App			Well ID		
		ATER WEL		Fraction		ection Num		Township Numb		ge Number	
County:				1/4 1/4 1	1/4 1/4	1 0				□ E □ W	
Business: di						treet or Rural Address where well is located (if unknown, distance and rection from nearest town or intersection): If at owner's address, check here:					
Address: Address:											
City:			State:	ZIP:							
3 LOCAT		ft. 5 Latitude :(decimal degrees)									
WITH " SECTIO	Depth(s) Gr	oundwater	ft.		Longitude:(decimal degrees)						
	N		2) ft. 3) ft., or 4) □ Dry V WELL'S STATIC WATER LEVEL:				um: 🗌] WGS 84 🛛 NAI	D 83 🗌 N	IAD 27	
			below land surface, measured on (mo-day-yr)					r Latitude/Longitude		``	
NW	NE		above land surface, measured on (mo-day-yr)				□ GPS (unit make/model:) (WAAS enabled? □ Yes □ No)				
		-	Pump test data: Well water was ft. after hours pumping gpm				□ Land Survey □ Topographic Map				
W	E	after			Online Mapper:						
CW CE				vater wass pumping							
	s	Estimated Y	6 J	6 Elevation:ft. □ Ground Level □ TOC <u>Source</u> : □ Land Survey □ GPS □ Topographic Map							
1 r	-	Bore Hole I	It. and ft.	<u></u>	Other						
7 WELL WATER TO BE USED AS:											
1. Domestic: 5. □ Public Water Supply: well ID											
			6. □ Dewatering: how many wells? 7. □ Aquifer Recharge: well ID				11. Test Hole: well ID				
Livest	Livestock 8. Monitoring			g: well ID		12. Geothermal: how many bores?					
	2. Irrigation 9. Environmental Remediation: v										
3. Eredlot Air Sparge 4. Industrial Recovery					Soil Vapor Extraction Injection			b) Open Loop □ Surface Discharge □ Inj. of Water 13. □ Other (specify):			
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:											
Water well disinfected? Yes No											
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded											
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
□ Steel □ Stainless Steel □ PVC □ Other (Specify)											
Brass Galvanized Steel None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Image: Comparison of the sector of											
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)											
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)											
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft. to ft.											
GRAVEL PACK INTERVALS: From ft. to ft., From ft., From ft., From ft. to ft. o ft. o ft. o ft.											
Grout Intervals: From											
Nearest source of possible contamination: No potential source of contamination within 200 ft.											
			Cess Pool	es		Livestock			ned Water		
□ Watertight Sewer Lines □ Seepage Pit □ Feedyard □ Fertilizer Storage □ Oil Well/Gas Well											
Direction from well? ft.											
10 FROM	TO		ITHOLO		FROM	ТО		ΓΗΟ. LOG (cont.) or	PLUGGIN	G INTERVALS	
					Notes:						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)											
Kansas Wa	iter Well Cor	itractor's Lice	ense No	This W	/ater Well R	ecord was c	omple	eted on (mo-day-ye	ear)		
	usiness name	e of									
Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565.											
Visit us at h	ttp://www.kdhe	ks.gov/waterwel	l/index.html						KS	SA 82a-1212	