

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BARTON		NW 1/4 NW 1/4 NE 1/4	30	T 19 S	R 12 EW
Distance and direction from nearest town or city street address of well if located within city? 1/4 MILE NORTH OF US. 56 OFF HWY 156 EAST SIDE MW# 4					
2 WATER WELL OWNER: CHASE PIPELINE CO.		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 37th ST. NORTH 4111		Application Number:			
City, State, ZIP Code: WICHITA, KS 67220					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 20 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter. 7 1/4 in. to 20 ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only ☒ 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR) ☒ 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile Welded 6 Asbestos-Cement 9 Other (specify below) Threaded ☒			
Blank casing diameter 2 in. to 10 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 24 in., weight sched 40 lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		☒ PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot ☒ Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 20 ft. to 10 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 20 ft. to 8 ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement ☒ 2 Cement grout ☒ 3 Bentonite 4 Other Grout Intervals: From 5 ft. to 0 ft., From 8 ft. to 5 ft., From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) ☒ 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage			
Direction from well? west		How many feet? 125			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	MEDIUM TO COARSE SAND			
5	6	DARK BRN CLAY			
6	7	BRN SILTY CLAY			
7	9	LIGHT BRN SILT			
9	11	CLAYEY SILT			
11	12	BRN PLASTIC CLAY			
12	15	LIGHT BRN FINE GRAINED SAND			
15	20	FINE TO MEDIUM GRAINED SAND SATURATED AT 12'			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-5-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 9-5-98 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					