

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton	NW ¼ NW ¼ SE ¼	30	T 19 S	R 12 E/W	
Distance and direction from nearest town or city street address of well if located within city? 36 NE Hwy 56, Great Bend					
2 WATER WELL OWNER: Doonan Truck					
RR#, St. Address, Box #: 551 S. Woodlawn			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code: Wichita, Kansas 67218			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 27 ft. ELEVATION:			
1 Mile N NW NE SW SE S W E		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL . . . 13 . . . ft. below land surface measured on mo/day/yr . . . 1/8/2009 . . . Pump test data: Well water was . . NA . . ft. after . . . hours pumping . . . gpm Est. Yield . . NA . . gpm; Well water was . . ft. after . . . hours pumping . . . gpm Bore Hole Diameter . . . 8 . . in. to . . . 27 . . . ft., and . . . in. to . . . ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued Clamped	
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)		Welded Threaded. ✓	
Blank casing diameter 2 in. to 20 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. . . . Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL					
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 30 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 18 ft. to 30 ft., From ft. to ft.					
From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 2.5 ft., From 2.5 ft. to 18 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
Direction from well?		How many feet?			
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	3	Topsoil,			
3	16	Clay, silty, Lt. Brown			
16	23	Sand (f-c) w/m gravel, clay stringers			
23	30	Sand (f-c) w/m gravel			
					MW6
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/8/2009 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 1/8/2009 under the business name of GeoCore, Inc. by (signature) Dan Hall					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					