

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Barton		SE ¼ SE ¼ SE ¼		30		T 19 S		R 12 EW	
Distance and direction from nearest town or city street address of well if located within city? ~3.5 mi. E of Great Bend on Barton County Rd.									
2 WATER WELL OWNER: Duoline Technologies, L.P. RR#, St. Address, Box # : 250 Blue Bird Lane City, State, ZIP Code : Gilmer, TX 75645 Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 15 ft ELEVATION: 1822.35						
			Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was NA ft. after hours pumping gpm Est. Yield NA gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 2.5 in. to 15 ft, and in. to ft WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes.....No✓ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ✓						
			5 TYPE OF BLANK CASING USED:						
			1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 4 in. to 10 ft, Dia in. to ft, Dia in. to ft Casing height above land surface -2.4 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 10 ft to 15 ft, From ft to ft GRAVEL PACK INTERVALS: From 8.5 ft to 15 ft, From ft to ft From ft to ft, From ft to ft						
			6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
			Grout Intervals: From 6 ft to 8.5 ft, From ft to ft, From ft to ft What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet?						
FROM TO LITHOLOGIC LOG					FROM TO PLUGGING INTERVALS				
0 0.5 Concrete,									
0.5 1 Sand, fill,									
1 4 Clay, Black									
4 6 Clay, Dark Brown									
6 11 Clay, sandy zone at 6.5-7', Brown									
11 11.5 Clay, Tan									
11.5 12 Sand, f-m, Tan									
12 15 Refusal,									
					MW17, Flushmount				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/17/2011 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 12/14/2011 under the business name of GeoCore, Inc. by (signature) Dale Bell									