

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

MW # 3

1

LOCATION OF WATER WELL:

County: Barton

Fraction: ~~SE~~ 1/4 ~~NE~~ 1/4 NW 1/4

Section Number: 30

Township Number: T 19 S

Range Number: R 12 E

Distance and direction from nearest town or city street address of well if located within city?

4 Miles East of Great Bend 1/2 mile N. of 56 & 156 Jct

2

WATER WELL OWNER:

RR#, St. Address, Box #: Koch Transportation Hwy 4111 East 37th St N

City, State, ZIP Code: Wichita KS 67220

Board of Agriculture, Division of Water Resources

Application Number:

3

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1 Mile

N

W

E

S

NW

NE

SW

SE

X

4

DEPTH OF COMPLETED WELL: 25 ft.

ELEVATION:

Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 7 1/4 in. to 25 ft. and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No: If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded

Blank casing diameter 2 in. to 10 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface 0 in. weight Sched 40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes

7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 25 ft. to 10 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

GRAVEL PACK INTERVALS: From 25 ft. to 8 ft. From ft. to ft.

From ft. to ft. From ft. to ft.

6

GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 6 ft. From 8 ft. to 3 ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

Direction from well? East

How many feet? 300'

FROM

TO

LITHOLOGIC LOG

FROM

TO

PLUGGING INTERVALS

0

1

Gravel Fill

1

3

Top Soil

3

7

Heavy Dark Red Silty Clay

7

12

Light Red Plastic Clay Moist

12

15

Ben to tan clay at 13

Very Plastic Very Moist

at 12.0

15

17

Medium Sand Saturated

at 15.0

17

25

Coarse Sand & Fine Gravel

7

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-16-95 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 5-30-95

under the business name of Kutz Environmental Service by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.