

Sparrows Well #1

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4

1/4

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Bartory</u>		<u>SE 1/4 SE 1/4 SW 1/4</u>	<u>28</u>	<u>T 19 S</u>	<u>R 13 EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>North east corner of 12th & Williams St Great Bend, KS</u>					
2 WATER WELL OWNER: <u>RPHIE</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # : <u>Forbes Field Bldg. 740 City of Great Bend</u>		Application Number:			
City, State, ZIP Code : <u>Topika KS 66620-0001</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>25.5</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>10</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: <u>7.44</u> in. to <u>25.5</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Sparrows Well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter <u>2</u> in. to <u>23</u> ft. Dia.		7 Fiberglass			
Casing height above land surface <u>0</u> in., weight <u>Sched 40</u> lbs./ft. Wall thickness or gauge No.		8 RMP (SR)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 2 Mill slot 3 Wire wrapped 4 Key punched 5 Torch cut 6 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>25.5</u> ft. to <u>23</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>25.5</u> ft. to <u>11</u> ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>8</u> ft. to <u>0.6</u> ft. From <u>11</u> ft. to <u>8</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? <u>52'</u>			
Direction from well? <u>South west</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
<u>0</u>	<u>6</u>	<u>Concrete</u>			
<u>6</u>	<u>1.0</u>	<u>Sand Fill</u>			
<u>1.0</u>	<u>5.0</u>	<u>Topsoil</u>			
<u>5.0</u>	<u>7.0</u>	<u>Ben Silty Sandy Clay</u>			
<u>7.0</u>	<u>10</u>	<u>Fine Sand Saturated at</u>	<u>10'</u>		
<u>10</u>	<u>15</u>	<u>Mid to Coarse Sand</u>			
<u>15</u>	<u>25.5</u>	<u>Coarse Sand w/ Fine to Mid Gravel</u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <u>(1)</u> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-21-95</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>575</u> This Water Well Record was completed on (mo/day/yr) <u>7-5-95</u> under the business name of <u>RUTH EXPLORATION SERVICE</u> by (signature) <u>[Signature]</u>					