

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Barton		NE 1/4 NE 1/4 NW 1/4	33	T 19 S	R 13 E 11
Distance and direction from nearest town or city street address of well if located within city? Steve's Conoco 10th & Main Great Bend, Ks.					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		Great Bend, Ks. 67530			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 7 1/2' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 7 1/2' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8 1/2" in. to 7 1/2' ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well OBSERVATION well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter: 2.375 in. to 4'3" ft., Dia		7 Fiberglass Welded X			
Casing height above land surface: Flush NE in., weight lbs./ft. Wall thickness or gauge No.		Threaded SDR 13 SCH 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 7 1/2' ft. to 4 1/2' ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 7 1/2' ft. to 3 1/2' ft. From ft. to ft.					
6 GROUT MATERIAL:		3 Bentonite 4 Other			
Grout Intervals: From 3 1/2' ft. to 2 1/2' ft. From 2 1/2' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet? 15'			
Direction from well? West					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Concrete			
.75	4	Dk gray silty sandy clay, dry to moist, faint to mod. odor, firm, fine grained sand.			
4	6	Olive sand & gravel, moist, odor, fine-coarse grained qtz. feldspar sand,			
6	7'6	olive green sandy clay len, moist, highly plastic, mod. odor.			
F.H. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-23-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 10-31-95 under the business name of JB Environmental Drilling by (signature) James Becker					