


1 LOCATION OF WATER WELL: County: Barton		Fraction NE 1/4 NE 1/4 NW 1/4	Section Number 33	Township Number T 19	Range Number S 13	EW
Distance and direction from nearest town or city street address of well if located within city? Golden Belt 66 10th & Main Great Bend, Ks.						
2 WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code		Duane Bird/Bird Oil 2001 10th St. Great Bend, Ks. 67503 Board of Agriculture, Division of Water Resources Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 20'6" ft. ELEVATION: Depth(s) Groundwater Encountered 1. 9' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 8.54 ft. below land surface measured on mo/day/yr 10-26-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" in. to 20'6" ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 2.375 in. to 10 ft., Dia Casing height above land surface 4.0 ft., weight lbs./ft. Wall thickness or gauge No. SDR 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 12 None used (open hole) 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20'6" ft. to 3' ft. From ft. to ft.		CASING JOINTS: Glued Clamped Welded Threaded X 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
6 GROUT MATERIAL: Grout Intervals: From 8' ft. to 5'6" ft. From 5'1" ft. to 0' ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? west How many feet? 20'		4 Other				
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS				
0	.50	Concrete w/ rebar				
.50	3.50	Dk gray silty sandy clay, firm, moist, mod. odor, fine grained sand.				
3.50	9.50	Fine grained gray sand, dry to moist, mod. odor, well rounded & sorted.				
9.50	20'6"	Moist to wet at 9'. Black sand & gravel, strong odor, well graded, poorly sorted.				
				F.M. OK'd by D. Taylor		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-24-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 10-21-95 under the business name of JB Environmental Drilling by (signature)						