

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number			
County: Barton		NW 1/4 NE 1/4 SW 1/4		33		T 19 S		R 13 EW			
Distance and direction from nearest town or city street address of well if located within city? 2133 Railroad Ave, Great Bend, KS											
2 WATER WELL OWNER: B.J. Services											
RR#, St. Address, Box # : 11211 W. FM 2920 MW-3 Board of Agriculture, Division of Water Resources											
City, State, ZIP Code : Tomball, TX 77375 Application Number:											
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 16 ft. ELEVATION:									
		Depth(s) Groundwater Encountered 1. 9 ft. 2. 9 ft. 3. 9 ft.									
		WELL'S STATIC WATER LEVEL 9.12 ft. below land surface measured on mo/day/yr 5/25/95									
		Pump test data: Well water was 9 ft. after 16 hours pumping 5/25/95 gpm									
		Est. Yield 8 gpm: Well water was 16 ft. after 16 hours pumping 5/25/95 gpm									
Bore Hole Diameter 8 in. to 16 ft., and 16 in. to 16 ft.											
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well											
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)											
2 Irrigation 4 Industrial 7 Lawn and garden only ☒ Monitoring well											
Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ If yes, mo/day/yr sample was submitted											
Water Well Disinfected? Yes ☒ No ☒											
5 TYPE OF BLANK CASING USED:											
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ☒ Clamped ☒											
☒ PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) ☒ Welded ☒ Threaded ☒											
7 Fiberglass											
Blank casing diameter 2 in. to 6 ft., Dia 6 in. to 6 ft., Dia 6 in. to 6 ft.											
Casing height above land surface 2 in., weight 6 lbs./ft. Wall thickness or gauge No. 6											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement											
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 10											
12 None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
1 Continuous slot ☒ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)											
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes											
7 Torch cut 10 Other (specify) 10											
SCREEN-PERFORATED INTERVALS: From 6 ft. to 16 ft., From 6 ft. to 16 ft., From 6 ft. to 16 ft.											
GRAVEL PACK INTERVALS: From 5 ft. to 16 ft., From 5 ft. to 16 ft., From 5 ft. to 16 ft.											
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other											
Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 5 ft., From 5 ft. to 5 ft.											
What is the nearest source of possible contamination:											
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well											
☒ Fuel storage 15 Oil well/Gas well											
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)											
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage											
Direction from well? Southwest How many feet? 70											
FROM		TO		LITHOLOGIC LOG		FROM		TO		PLUGGING INTERVALS	
0		1.5'		Gravel (fill)							
1.5'		3.0'		clay, w/silt, brn							
3.0'		16.0'		sand, medium to coarse grained w/gravel, brn							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☒ reconstructed, or ☒ plugged under my jurisdiction and was completed on (mo/day/year) 5/24/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 438 This Water Well Record was completed on (mo/day/yr) 6/28/95 under the business name of Kansas City Testing Lab by (signature) Charles Harper											