

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Barton		NW 1/4 NW 1/4 NE 1/4		14		T 19 S		R 13 E/W	
Distance and direction from nearest town or city street address of well if located within city? Approx. 1 1/2 mile north and 1 1/2 mile east of Great Bend, KS									
2 WATER WELL OWNER:		Community Christian Church							
RR#, St. Address, Box # :		Box 333							
City, State, ZIP Code :		Great Bend, KS 67530							
Board of Agriculture, Division of Water Resources Application Number: not required									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 153 ft. ELEVATION: unknown							
1 Mile		Depth(s) Groundwater Encountered 1. 80 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 80 ft. below land surface measured on mo/day/yr 6-29-84							
		Pump test data: Well water was not ok'd. ft. after hours pumping gpm							
		Est. Yield Unknown gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter .9 in. to 1.53 ft. and in. to ft.							
TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 5 in. to 80 ft. Dia 5 in. to 138 ft. Dia in. to ft.									
Casing height above land surface 24 in., weight 2.277 lbs./ft. Wall thickness or gauge No. .214									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS:		From 80 ft. to 90 ft. From ft. to ft.							
From 138 ft. to 153 ft. From ft. to ft.									
GRAVEL PACK INTERVALS:		From 25 ft. to 153 ft. From ft. to ft.							
Annular fill From 10 ft. to 21 ft. From ft. to ft.									
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout intervals: From 0 ft. to 10 ft. From 21 ft. to 25 ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? East		How many feet? 100							
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG			
0	59	Topsoil & soft brown clay							
59	64	Dakota drift							
64	90	Soft sandstone							
90	140	White & red & gray Dakota clay w/a few thin streaks of sandstone between 110'-120' and 123' & 128'							
140	143	Sandstone							
143	146	Gray clay							
146	153	Sandstone, soft, coarse looking sandstone							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-29-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo/day/yr) 8-9-84 under the business name of CLARKE WELL & EQ., INC. by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									