

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Barton	NW 1/4 NE 1/4 NW 1/4	16	T 19 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

Hwy 281 North; Great Bend

2 WATER WELL OWNER:	RR#, St. Address, Box #:	City, State, ZIP Code:	Board of Agriculture, Division of Water Resources
Sanice Roughton	20 Northridge	Shawnee OK 74801	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL:	ELEVATION:
	Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.	ft.
	WELL'S STATIC WATER LEVEL 12.18 ft. below land surface measured on mo/day/yr	2-25-93
	Pump test data: Well water was ft. after hours pumping gpm	
	Est. Yield gpm Well water was ft. after hours pumping gpm	
	Bore Hole Diameter 8 in. to ft. and in. to ft.	
	WELL WATER TO BE USED AS:	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No X	
	Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded Flush
Blank casing diameter in. to ft. Dia in. to ft. Dia in. to ft.			
Casing height above land surface Flush in. weight 703 lbs./ft. Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 8.0 ft. to 18.0 ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	
GRAVEL PACK INTERVALS:	From 7.0 ft. to 18.0 ft.	From ft. to ft.	
	From ft. to ft.	From ft. to ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
GROUT INTERVALS:	From 7.0 ft. to 1.0 ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? SE				How many feet? 130

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	10.0	Clay, slightly silty			
10.0	18.0	silt, sandy, tan			
Flush Mount Waiver granted on 12-17-92 for R&S Mini Mart; KDHE 06005260 by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-25-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3-8-93 under the business name of GSI by (signature) Allison J. J. J.
--