

1) LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Barton		1/4 N 1/2 1/4 SE 1/4		16		T 19 S		R 13 E/W	
Distance and direction from nearest town or city street address of well if located within city? Rt. 1- Bomar addition, city of Great Bend, Ks.									
2) WATER WELL OWNER:		Erma Zimmerman				Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Rt. 1-Bomar Homes				Application Number: 796			
City, State, ZIP Code :		Great Bend, Ks. 67530							
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4) DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 13 ft. below land surface measured on mo/day/yr 5-19-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield na gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 10 in. to 60 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes hth No							
5) TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile							
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded							
Blank casing diameter 5 in. to 40 ft. Dia in. to ft. Dia in. to ft.		7 Fiberglass Threaded							
Casing height above land surface 2' in. weight .258 lbs./ft. Wall thickness or gauge No.		TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement							
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 20 ft. to 60 ft. From ft. to ft.							
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug		Grout Intervals: From 3 ft. to 14 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well		3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
Direction from well? south		How many feet? 100							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 Top soil									
3 14 Gray clay									
14 18 Sand									
18 23 Clay									
23 26 Sand and gravel									
26 27 Clay									
27 32 Sand and gravel									
32 33 Clay									
33 42 Sand and gravel									
42 43 Clay									
43 50 Sand and gravel									
50 51 Clay									
51 62 Sand and gravel									
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-26-94 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 6-7-94									
under the business name of Rosencrantz-Bemis by (signature) Fredia Heddon									
INSTRUCTIONS: Use typewriter or ball point pen PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									