

1 LOCATION OF WATER WELL: County: Barton		Fraction SE 1/4 NE 1/4 SE 1/4		Section Number 28		Township Number T 19 S		Range Number R 13 E W	
Distance and direction from nearest town or city street address of well if located within city? 1400 Broadway Great Bend, KS. 67530									
2 WATER WELL OWNER: Hays & Great Bend Fire Extinguisher Co.									
RR#, St. Address, Box #: 127 E. 8th Hays, Ks. 67601						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code:						Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 15'6" ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 7' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 5.65 ft. below land surface measured on mo/day/yr 2-1-94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7 1/2" in. to 15'6" ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2.375 in. to 5' ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface Flush Ground in. weight lbs./ft. Wall thickness or gauge No. SDR-13 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement SCH 40 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From 15' ft. to 5' ft. From ft. to ft. GRAVEL PACK INTERVALS: From 15'6" ft. to 3'6" ft. From ft. to ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 3'6" ft. to 2'6" ft. From 2'6" ft. to 0' ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage Fueler 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? North East How many feet? 110'									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 1 Dk. brown loamy soil, frozen, earthy odor.									
1 5.50 Tanish brn silty clay, mottled w/ light gray chalky caliche stringers. Few ls. rx frag. Friable w/ uncreasing fine grained sand around 5'.									
5.50 15.50 Tan fine-med. grained sand, Subrounded, moist to wet. Well graded									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-1-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 2-21-94 under the business name of JB Environmental Drilling by (signature) James Bieker									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									
