

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: BOGOTON		$\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$	29	T 19 S	R 13 EW
Distance and direction from nearest town or city street address of well if located within city? 3600 Robin Road					
2 WATER WELL OWNER: Eugene J. Zorn		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: 3600 Robin Road		Application Number:			
City, State, ZIP Code: Gage Bend, Kans. 67530					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 28' 4" ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 15 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 7-19-88			
		Pump test data: Well water was 15 ft. after hours pumping gpm			
		Est. Yield 50 gpm: Well water was 18 ft. after hours pumping gpm			
		Bore Hole Diameter 6 in. to 14 ft., and 5 in. to 28 ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial ⑦ Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No If yes, mo/day/yr sample was submitted 8-31-88; 8-9-88			
		Water Well Disinfected? Yes ☒ No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) CASING JOINTS: Glued ☒ Clamped ② PVC 4 ABS 7 Fiberglass Welded Threaded					
Blank casing diameter 5 in. to 28 ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 375					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot ③ Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 28 ft. to 18 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 28 ft. to 26.5 ft., From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement ② Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 15 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well ③ Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage 					
Direction from well? South How many feet? 18					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0'	7'	Fill Sand			
7'	15'	Coarse Sand			
15'	28' 3/4"	Finer Sand			
28' 3/4"	28' 4"	Clay			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-19-88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) 7-19-88 under the business name of by signature Eugene J. Zorn					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					