

1 LOCATION OF WATER WELL:		Fraction SE ¼ SE ¼ SW ¼	Section Number 30	Township Number T 19 S	Range Number R 13 EW
County: Barton					
Distance and direction from nearest town or city street address of well if located within city? 5200 West 10th Street, Great Bend, Kansas					
2 WATER WELL OWNER: Allen Scheck		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: P.O. Box 687		Application Number:			
City, State, ZIP Code: Hays, Ks. 67601					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 13 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL NA ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 7 5/8 in. to 29 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was sub-			
		mitted Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter 2 in. to 9 ft. Dia in. to ft. Dia in. to ft.		7 Fiberglass Threaded X			
Casing height above land surface 0 in. weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 9 ft. to 29 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 7 ft. to 29 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 2 ft. From 2 ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? west		How many feet? 5			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6"	concrete			
6"	2'	sandy clay, dark brown, moist			flush mount cover
2'	4'	sand, dark brown, damp, fine to coarse			OB1
4	6	sand, brown, damp, fine to medium			
6	12	sand, grey brown, fine to coarse			
12	18	sand-gravel, grey brown, fine granule, saturated			
18	29	sand-gravel, brown, fine pebbles, saturated			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-26-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-19-93 under the business name of GeoCore Services, Inc. by (signature) Doug Roy					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					