

1 LOCATION OF WATER WELL		Fraction		Section Number		Township Number		Range Number	
County: Barton		SE 1/4 SE 1/4 SE 1/4		30		T 19 S		R 13 E/W	
Distance and direction from nearest town or city?					Street address of well if located within city?				
					4107 10th				
2 WATER WELL OWNER: Dillons									
RR#, St. Address, Box # : 4107 10th					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Great Bend, Ks. 67530					Application Number:				
3 DEPTH OF COMPLETED WELL: 8.0 ft. Bore Hole Diameter: 12 1/4 in. to 8.0 ft., and in. to ft.									
Well Water to be used as:									
1 Domestic		3 Feedlot		5 Public water supply		8 Air conditioning		11 Injection well	
2 Irrigation		4 Industrial		6 Oil field water supply		9 Dewatering		12 Other (Specify below)	
		0 Lawn and garden only		10 Observation well					
Well's static water level: 19 ft. below land surface measured on 10 month 15 day 80 year									
Pump Test Data: Well water was ft. after hours pumping gpm									
Est. Yield NA gpm: Well water was ft. after hours pumping gpm									
4 TYPE OF BLANK CASING USED:									
1 Steel		3 RMP (SR)		5 Wrought iron		8 Concrete tile		Casing Joints: Glued X Clamped	
0 PVC		4 ABS		6 Asbestos-Cement		9 Other (specify below)		Welded	
				7 Fiberglass				Threaded	
Blank casing dia: 6 in. to 60 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface: 12 in., weight lbs./ft. Wall thickness or gauge No. 280									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)		10 Asbestos-cement	
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS		11 Other (specify)	
								12 None used (open hole)	
Screen or Perforation Openings Are:									
1 Continuous slot		3 Mill slot		5 Gauzed wrapped		8 Saw cut		11 None (open hole)	
2 Louvered shutter		4 Key punched		6 Wire wrapped		9 Drilled holes			
				7 Torch cut		10 Other (specify)			
Screen-Perforation Dia: 6 in. to 80 ft., Dia in. to ft., Dia in. to ft.									
Screen-Perforated Intervals: From 60 ft. to 80 ft., From ft. to ft., From ft. to ft.									
Gravel Pack Intervals: From 10 ft. to 80 ft., From ft. to ft., From ft. to ft.									
5 GROUT MATERIAL:									
0 Neat cement		2 Cement grout		3 Bentonite		4 Other			
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank		4 Cess pool		7 Sewage lagoon		10 Fuel storage		14 Abandoned water well	
0 Sewer lines		5 Seepage pit		8 Feed yard		11 Fertilizer storage		15 Oil well/Gas well	
3 Lateral lines		6 Pit privy		9 Livestock pens		12 Insecticide storage		16 Other (specify below)	
Direction from well: East How many feet: 75 ? Water Well Disinfected? Yes HTH No									
Was a chemical/bacteriological sample submitted to Department? Yes X No If yes, date sample was submitted 10 month 16 day 80 year Pump Installed? Yes No X									
If Yes: Pump Manufacturer's name Model No. HP Volts									
Depth of Pump Intake ft. Pumps Capacity rated at gal. min.									
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other									
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 10 month 16 day 80 year									
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134									
This Water Well Record was completed on 10 month 28 day 80 year under the business name of Rosentantz-Bemis by (signature) Nora Rodson									
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:									
		FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG		
		0	3	Top sandy soil					
		3	33	Sand and gravel					
		33	35	Sand and gravel mixed w/yellow and gray clay					
		35	45	Yellow and gray clay					
	45	80	Sand and gravel						
ELEVATION:									
Depth(s) Groundwater Encountered 1. 19 ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)									

OFFICE USE ONLY

T

19

R

13

EN

SEC

30

SE

1/4

SE

1/4

SE

1/4