


1 LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 NE 1/4 Section Number 32 Township Number 19 S Range Number 13 E  
 County: Barton Distance and direction from nearest town or city street address of well if located within city?

2701 10th Street

2 WATER WELL OWNER: Teacher's Insurance Annuity Assoc.  
 RR#, St. Address, Box #: 730 Third Ave  
 City, State, ZIP Code: New York NY 10017  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:   
 4 DEPTH OF COMPLETED WELL: 17 ft. ELEVATION: 2-26-93  
 Depth(s) Groundwater Encountered: 8.4 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 8.4 ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 8 in. to ft. and in. to ft.  
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded  
 2 PVC 4 ABS 7 Fiberglass Threaded Flush  
 Blank casing diameter: 2 in. to ft. Dia. in. to ft. Dia. in. to ft.  
 Casing height above land surface: Flush in. weight: 1703 lbs./ft. Wall thickness or gauge No. 154  
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 6 ft. to 17 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 6 ft. to 1 ft. From ft. to ft. From ft. to ft.  
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage  
 Direction from well? SE How many feet? 50

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS  
 0.0 0.5 Concrete  
 0.5 8.5 Clayey silt  
 8.5 10.0 Silty sand, clayey, orange brown  
 10.0 17.0 Sand coarse to medium  
 some gravel  
 Flush mount waiver granted 3-24-93  
 for Bob's Finca; KDHE 0605508  
 by Don Taylor

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-25-93 and this record is true to the best of my knowledge and belief. Kansas  
 Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 3-26-93  
 under the business name of GSI by (signature) Allison Ivins