

MW-2

2011087

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Barton</u>	<u>NW 1/4 NE 1/4 NE 1/4</u>	<u>32</u>	<u>T 19 S</u>	<u>R 13 E</u>

Distance and direction from nearest town or city street address of well if located within city?

2701 10th Street

2 WATER WELL OWNER:	RR#, St. Address, Box #	City, State, ZIP Code	Board of Agriculture, Division of Water Resources
	<u>Teachers Insurance Annuity Assoc</u>	<u>730 Third Ave</u>	
	<u>New York NY</u>	<u>10017</u>	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	18 ft. ELEVATION:
	Depth(s) Groundwater Encountered	10 ft.
	WELL'S STATIC WATER LEVEL	8.2 ft. below land surface measured on mo/day/yr
	Pump test data: Well water was	ft. after hours pumping gpm
	Est. Yield gpm: Well water was	ft. after hours pumping gpm
	Bore Hole Diameter	8 in. to ft., and in. to ft.
	WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
	Was a chemical/bacteriological sample submitted to Department? Yes No X	If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded Threaded Flush
Blank casing diameter	in. to ft. Dia	in. to ft. Dia	in. to ft. Dia
Casing height above land surface	Flush in. weight	703 lbs. ft. Wall thickness or gauge No.	154
TYPE OF SCREEN OR PERFORATION MATERIAL:	1 Steel	3 Stainless steel	5 Fiberglass
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	1 Continuous slot	3 Mill slot	5 Gauzed wrapped
2 Louvered shutter	4 Key punched	7 Torch cut	8 Saw cut
SCREEN-PERFORATED INTERVALS:	From 8 ft. to 18 ft.	From 18 ft. to 18 ft.	From 18 ft. to 18 ft.
GRAVEL PACK INTERVALS:	From 7 ft. to 18 ft.	From 18 ft. to 18 ft.	From 18 ft. to 18 ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From ft. to ft.	From ft. to ft.	From ft. to ft.	From ft. to ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well?	NE		13 Insecticide storage	16 Other (specify below)
			How many feet?	50

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	0.5	Concrete			
0.5	8.5	Layered sands, sandy silts & silts			
8.5	10.0	Silty sand			
10.0	18.0	Sands, medium to coarse w/ some gravel			
Flushmount waiver granted 3-24-93 for Bob's Finca; KDHE 0605508 by Don Taylor					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)	3-25-93	and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No.	531	This Water Well Record was completed on (mo/day/yr)	3-26-93
under the business name of	GST	by (signature)	Allison Irwin

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.